

Majic Latex Field Marking Paint

8-0010

DESCRIPTION

Majic Latex Field Marking Paint is a ready to use, fast drying formula, designed for lining and marking natural surfaces.



FEATURES

- Fast drying
- Ready to use
- For temporary marking of athletic fields

VOC / MIR (sprays)

100 gm/l
(0.83 lbs/gal)

NET WEIGHT

10.2 lbs/gal

AVAILABLE SIZES

5-gallon

SHIPPING WT

5-gal pail/53 lbs

AVAILABLE COLORS

8-0010 White

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 30 minutes	DRYTIME-RECOAT n/a	WET/ FILM THK 5.0 mils	FILM THK /DRY: 1.0 mils	FINISH Flat	GLOSS < 5@ 60°
FLASHPOINT > 200° F	COVERAGE 1750 to 2000 sq ft/5 gal	VISCOSITY 92 - 98 KU	VEHICLE Vinyl Acrylic Latex	SOLVENT Water/Glycol	

SURFACE PREP

When painting a field where the grass is abnormally dry, water the field and allow the water to be absorbed prior to applying any field marking paint. This will prevent the grass from absorbing water directly from the coating which, under some circumstances, can cause the lines to appear burnt in. The surface should be clean of debris. Cut grass to desired level and perform all preliminary preparations to the field surface before lines are marked. If surface is wet from rain, dew or watering, allow to dry thoroughly before application.

APPLICATION

Stir well before using. This product can be applied by a line marking machine, brush, roller or spray. Temperature should be above 50° F.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.