

# Majic Durable Bright Aluminum Paint

8-0020

## DESCRIPTION

A ready-mixed, ready-to-use aluminum paint formulated with the finest grade leafing aluminum pigments, long wearing oils and synthetic resins.



## FEATURES

- Applies easily with brush, roller or spray
- Leafing evenly to a bright finish
- Dries in just 4 hours
- Heat resistant up to 600° F
- Rust inhibiting

## VOC / MIR (sprays)

500 gm/l  
(4.20 lbs/gal)

## NET WEIGHT

7.6 - 7.8 lbs/gal

## AVAILABLE SIZES

5-gallon, gallon,  
quart

## SHIPPING WT

5-gal pail/42.75 lbs  
4-gal case/35 lbs  
4-qt case/9.5 lbs

## AVAILABLE COLORS

8-0020 Aluminum

## SHIPPING RESTRICTION

None

## PRODUCT STATISTICS

<b>DRYTIME-TOUCH</b> 5-10 hours	<b>DRYTIME-RECOAT</b> 24 hours	<b>WET/ FILM THK</b> 2.4 mils	<b>FILM THK /DRY:</b> 1.0 mils	<b>FINISH</b> Aluminum	<b>GLOSS</b> n/a
<b>FLASHPOINT</b> > 105° F	<b>COVERAGE</b> Up to 600 sq ft/gal	<b>VISCOSITY</b> 20 - 30 sec, Zahn #2	<b>VEHICLE</b> Petroleum Resin/Alkyd	<b>SOLVENT</b> Mineral Spirits	

## SURFACE PREP

All surfaces to be painted must be clean, dry and free of oil, grease, or rust. Loose rust and scale should be removed with wire brush or sandpaper. Clean new metal with rags saturated with mineral spirits to remove grease or oily residue. Remove loose, scaling & peeling paint by scraping or sanding. To assure a good adhesion, glossy surfaces should be dulled. New masonry surfaces should be allowed to age at least 90 days before painting. Use a wire brush to remove loose sand and mortar. Recommended uses: Interior or exterior metal, wood or masonry surfaces. Recommended for radiators, boilers, smoke stacks and other surfaces where a heat-resistant coating is necessary. This coating derives its brilliance from a surface leafing pigment. Therefore it should not be used on any surface subject to abrasion or constant rubbing.

## APPLICATION

Blend the paint by pouring off the top half to two-thirds of the paint into a separate container. Stir the remainder to a uniform consistency, making sure that all aluminum pigments are evenly dispersed. Add the removed portion back into the can while mixing thoroughly. Stir occasionally during application. Apply the paint with a good quality polyester brush, short nap roller, or spray equipment. The paint should be applied liberally, finishing off in one direction. Exterior paint should not be attempted in damp or rainy weather or when temperatures are below 50° F. Do not apply to hot surfaces. DO NOT THIN

## WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.