

Majic Latex Barn & Fence Paint

8-0046 Series

DESCRIPTION

This is a high-hiding barn latex paint combining long lasting weather resistance and excellent color retention. Use Majic Latex Barn & Fence Paint on properly prepared wood, masonry or metal. DO NOT USE ON ROOFS OR FLOORS.



FEATURES

- Fade resistant
- Dries bug-free in 30 minutes
- Weather resistant
- Lead & mercury FREE
- Soap & water cleanup

VOC / MIR (sprays)

100 gm/l
(0.83 lbs/gal)

NET WEIGHT

9.86 lbs/gal

AVAILABLE SIZES

5-gallon, gallon

SHIPPING WT

5-gal pail/51.3 lbs
4-gal case/43 lbs

AVAILABLE COLORS

8-0046 White, 8-0047 Classic Red, 8-0048 Black

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 1 to 2 hours	DRYTIME-RECOAT 6 hours	WET/ FILM THK 5.3 mils	FILM THK /DRY: 1.0 mils	FINISH Flat	GLOSS < 5 @ 60°
FLASHPOINT > 200°F	COVERAGE Up to 250 sq ft/gal	VISCOSITY 85 - 95 KU	VEHICLE Vinyl Acrylic Latex	SOLVENT Water	

SURFACE PREP

New Wood: Seal knots with a pigmented shellac primer. Prime with an exterior wood primer. Allow to dry 24 hours before applying the finish coat. Previously Painted Wood: Remove all loose and peeling paint, chalk, dirt, and mildew. Mildew can be removed by using a solution of bleach and water or a special mildew cleaner. The use of a power washer equipped with a detergent injector may be helpful on large projects. Dull any glossy area with sandpaper. Spot prime bare areas with an exterior wood primer. Masonry: Remove loose mortar, peeling paint and other foreign material with a wire brush. Remove chalk and dirt by washing and rinse thoroughly. You may observe white stains or deposits on the masonry. This is known as efflorescent salts and must be removed with a solution of muriatic acid and water. Once the surface is clean proceed with two coats of Majic Latex Barn Paint. New masonry surfaces should be allowed to weather for at least 60 days and then neutralized with 10% muriatic acid before painting. Metal: Clean off any rust, peeling paint. Prime bare areas with red metal primer or Rust Kill Primer.

APPLICATION

Stir paint thoroughly. If thinning is required use water sparingly (maximum 1 pint/gallon). The surface should be clean and properly prepared as described above. Do not apply to a hot surface or if temperatures are to fall below 60°F, or when rain is expected within 24 hours. Time your work so that you can stop painting by at least 4 hours before nightfall. Avoid painting in direct sunlight. Apply paint generously with a good quality brush or roller. Two coats may be required on a textured or porous surface or where there is a radical color change.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.