

Majic Quick Dry Latex Stain Blocking Primer Sealer

8-0059

DESCRIPTION

Majic Quick Dry Latex Stain Blocking Primer Sealer is a fast drying, water-based primer for interior and exterior use. This product will block out most stains including asphalt, water, rust, grease, ink, pencil and felt marker. Perfect for use on woodwork, drywall, plaster, paneling, wallpaper, masonry, brick, painted metal and properly prepared glossy surfaces. It can be top-coated with latex or oil based paint. It is not recommended on flooring.



FEATURES

- Seals interior and exterior woodwork, drywall, plaster, paneling, wallpaper, masonry, brick, painted metal and properly prepared glossy surfaces
- Ideal for color changes
- For use under alkyd or latex finish coats

VOC / MIR (sprays)

200 gm/l
(1.66 lbs/gal)

NET WEIGHT

11.0 lbs

AVAILABLE SIZES

gallon

SHIPPING WT

4-gal case/43 lbs

AVAILABLE COLORS

8-0059 White

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 30 minutes	DRYTIME-RECOAT 1-2 hours	WET/ FILM THK 3.0 mils	FILM THK /DRY: 1.0 mil	FINISH Flat	GLOSS 0-5 @ 60°
FLASHPOINT < 200° F	COVERAGE Up to 400 sq ft/gal	VISCOSITY 90 - 95 KU	VEHICLE Acrylic Latex	SOLVENT Water	

SURFACE PREP

The surface must be clean, dry and free of peeling paint, loose rust, excessive chalk, wax or mildew. Remove loose wallpaper and wallpaper paste. If washing is necessary, use a non-soapy detergent such as trisodium phosphate (TSP). Rinse well and allow to dry completely. Unpainted, exterior wood exposed to sun and/or moisture longer than 2-4 weeks, must be cleaned and sanded before priming. Scuff sand any glossy surfaces before priming. Remove any mold or mildew using one quart of household bleach in three quarts of water. Rinse thoroughly and let dry. Wear goggles and gloves to prevent contact with the bleach. Majic Stain Blocking Primer can be used on clean, dry, aged masonry surfaces. New masonry must be allowed to cure for at least 30 days before priming.

APPLICATION

Stir the paint thoroughly. Apply with brush, roller or spray. When brushing, best results are obtained with a good bristle brush. If rolling, use a short nap roller for best appearance. Do not apply too heavily. A good even coat will assure effective stain kill. This product comes ready to use and should not be thinned. After sealing stained areas with this product, test a small section with application of the finish coat. If the stain bleeds through, apply a second coat of Majic Quick Dry Primer Sealer and retest. Do not apply if temperature is below 50° F. DO NOT THIN.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.