

Town & Country Tank Enamel

8-0064

DESCRIPTION

Town & Country Oil Base Tank Enamel is a durable, heavy duty alkyd enamel specially formulated for excellent adhesion, and resistance to weathering and corrosion.



FEATURES

- Excellent adhesion
- Resistant to weathering and corrosion
- Perfect for use on iron, steel, aluminum & galvanized metal
- Complies with applicable DOT regulations for propane tanks

VOC / MIR (sprays)

400 gm/l
(3.33 lbs/gal)

NET WEIGHT

10.81 lbs/gal

AVAILABLE SIZES

5-gallon, gallon

SHIPPING WT

5-gal pail/51.3 lbs
4-gal case/43 lbs

AVAILABLE COLORS

8-0064 White

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 5 - 10 hours	DRYTIME-RECOAT 24 hours	WET/ FILM THK 2.5 mils	FILM THK /DRY: 1.3 mils	FINISH Gloss	GLOSS 80+ @ 60°
FLASHPOINT > 105° F	COVERAGE Up to 600 sq ft/gal	VISCOSITY 83 - 88 KU	VEHICLE Alkyd	SOLVENT Mineral Spirits	

SURFACE PREP

All Surfaces, new or previously painted, must be clean, dry and free of oil, dirt, grease, mildew and rust. Rusted Metal should be cleaned with a wire brush or sandpaper. Remove loose, scaling paint by wire brushing, scraping or sanding. Glossy surfaces and all protected areas not exposed to normal weathering should be dulled by sanding. Remove oil residues from new metal surfaces by cleaning with rags saturated in mineral spirits. Surfaces with extensive rust or heavy oxidation should be cleaned to remove loose scale, dust and debris. Ferrous Metal - Prime with a rust inhibiting primer. For extra protection, spot prime welded joints and intersections with the primer. Then follow with one full primer coat over the entire surface. Galvanized Metal - On galvanized metal that is new or in sound condition, apply one coat of an appropriate primer.

APPLICATION

Stir the paint thoroughly. Apply with brush, roller or spray. When brushing, best results are obtained with a good bristle brush. If rolling, use a short nap roller for best appearance. Do not apply too heavily. A good even coat will assure effective stain kill. This product comes ready to use and should not be thinned. After sealing stained areas with this product, test a small section with application of the finish coat. If the stain bleeds through, apply a second coat of Majic Quick Dry Primer Sealer and retest. Do not apply if temperature is below 50° F. DO NOT THIN.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.