

# Majic Waterproofing Clear Sealer

8-0065

## DESCRIPTION

Majic Waterproofing Sealer is a clear, non-staining sealer for dry porous materials. Majic Waterproofing Sealer penetrates into the surface to produce a year-round waterproof barrier in wood, concrete, masonry, and stucco. This product prevents concrete and masonry damage such as spalling, fracturing and efflorescence. Use on wood to eliminate warping, twisting, grain raising, splitting, shrinkage and moisture related deterioration.



## FEATURES

- Clear and non-staining sealer
- Blocks moisture from penetrating into the surface
- Prevents swelling and shrinking of wood
- Rubber base formula provides superior penetration, durability and water beading properties

## VOC / MIR (sprays)

600 gm/l  
(5.00 lbs/gal)

## NET WEIGHT

6.7 lbs/gal

## AVAILABLE SIZES

5-gallon, gallon

## SHIPPING WT

5-gal pail/37.3 lbs  
4-gal case/30.5 lbs

## AVAILABLE COLORS

8-0065 Clear

## SHIPPING RESTRICTION

CA, OTC

## PRODUCT STATISTICS

<b>DRYTIME-TOUCH</b> 24 - 48 hours	<b>DRYTIME-RECOAT</b> 7 days to stain	<b>WET/ FILM THK</b> 5.2 mils	<b>FILM THK /DRY:</b> 1.3 mils	<b>FINISH</b> Clear	<b>GLOSS</b> n/a
<b>FLASHPOINT</b> > 105° F	<b>COVERAGE</b> See label - up to 300 sq ft	<b>VISCOSITY</b> 28 - 32 #1 Zahn Cup	<b>VEHICLE</b> Alkyd	<b>SOLVENT</b> Mineral Spirits	

## SURFACE PREP

Allow New Concrete to age for at least 6 months. The surface should be neutralized and etched with a 5% to 10% muriatic acid solution. Rinse thoroughly with clean water. All surfaces must be clean and firm. Wear goggles and gloves to prevent contact with the muriatic acid. Remove all previous finishes by appropriate means. Remove grease and oil with a degreaser or solvent. Remove dust and dirt with a low sudsing detergent or high pressure wash. Allow all surfaces to dry thoroughly. Adequate drying may require 2 to 3 days under some conditions. Majic Waterproofing Sealer is a solvent based product and may cause bleeding of internal color in white bricks and certain color coatings on stucco and masonry. Test a small area to insure compatibility before proceeding. Use a block filler on highly porous cinder block before applying this product.

IMPORTANT NOTES: Do not use this product below grade or other areas where water pressure may exist. Do not use on rubber, asphalt base materials or certain plastics and synthetics. Apply a test patch if unsure. Do not expose freshly treated articles to fire or flame. Protect plants with plastic or canvas drop cloths. Some water based adhesives will bond to waterproofed surfaces.

## APPLICATION

Stir well before using. A test patch to insure compatibility is recommended before coating entire surface. Apply generously with brush, roller or low pressure spray to point of saturation without leaving any excess on horizontal areas. Temperature should be above 40° F. Majic Waterproofing Sealer may be applied on previously painted surfaces if porous enough to allow penetration of sealer. It also makes an excellent undercoat for all type of oil base and latex primers and finish paints. Two coats are recommended on surfaces that are not to be painted. Allow the first coat to dry 48 hours before recoating.

## WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.