

Majic Solid Color Latex House & Deck Stain

DESCRIPTION

Majic Solid Color House & Deck Stain provides a mildew resistant, water repellent coating for pressure treated and untreated wood, decks, siding and fences. Beautiful semi-transparent colors protect wood against moisture, swelling, cracking, warping, splintering and discoloration.

FEATURES

- Superior protection for exterior wood
- Provides excellent water repellency
- Perfect for deck floor boards, rails, spindles, fences, decorative trim, wood lawn furniture, and exterior wood siding

VOC / MIR (sprays)

250 gm/l
(2.08 lbs/gal)

AVAILABLE SIZES

gallon

AVAILABLE COLORS

8-0221 Cedar, 8-0223 Cape Cod Gray, 8-0224 Redwood, 8-0226 Russet Brown

NET WEIGHT
11.5 lbs/gal

SHIPPING WT
4-gal case/45 lbs

SHIPPING RESTRICTION
CA



PRODUCT STATISTICS

DRYTIME-TOUCH 2-4 hours	DRYTIME-RECOAT 24 hours	WET/ FILM THK 4.0 mils	FILM THK /DRY: 1.5 mils	FINISH Matte	GLOSS n/a
FLASHPOINT > 200° F	COVERAGE Up to 300 sq ft/gal	VISCOSITY 90 - 94 KU	VEHICLE Vinyl Acrylic Latex	SOLVENT Water	

SURFACE PREP

New Wood Surfaces: Make sure surface is dry and clean, free of dirt, dust and mildew. Check dryness of surface by sprinkling water on wood to be stained. If the water is absorbed rapidly into surface, wood is ready for Majic House & Deck Stain application. If water is not rapidly absorbed into surface, allow the wood to weather two to three days and test again. Clean soil stains on newly constructed wood projects before applying Majic House & Deck Stain. **Older Weathered Wood Surfaces:** Beautify and protect older weathered wood by applying Majic House & Deck Stain. Make sure wood surface is dry and clean, free of dirt, dust and mildew. Clean and prepare older, weathered-gray wood surfaces to allow for better stain penetration, pigment adhesion, and cleaner, brighter color results. **Previously Stained Wood Surfaces:** Make sure wood surface is dry and clean, free of dirt, dust, and mildew. Clean and prepare previously stained wood. Apply a similar or dark color shade of stain to renew protection and beauty of wood.

APPLICATION

Majic House & Deck Stain should be shaken or stirred thoroughly before use. Do not dilute with additional water. Stir occasionally during use. Apply Majic House & Deck Stain by brush, roller or spray. Back brushing is recommended when spraying to assure uniform coverage and appearance. Use on exterior surfaces only. Protect vegetation from over spray and drippage. Do not apply Majic House & Deck in direct sunlight or when temperature is below 50° F. Before use, test on a small area of surface to preview color appearance. Allow to dry in precipitation-free weather for 24 hours. To minimize lap marks, stain three to four boards, always working from the wet edge of the job. One coat coverage is normally adequate. The color of this product may vary dependent on species of wood, age, graying, grain pattern, heartwood content, number of applied coats and thoroughness or mixing.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.