


# Majic Oil Base Polyurethane Wood Varnish

**8-0310 Series**

## DESCRIPTION

This is a hard protective, clear varnish that offers exceptionally long lasting beauty on wood surfaces subject to wear and abuse. It enriches the natural beauty of wood while providing protection from abrasion, water, alcohol, cleaners and stains. Majic Oil Base Polyurethane Wood Varnish is available in high gloss or natural satin finish for a rich hand-rubbed appearance.



## FEATURES

- For all interior wood surfaces
- Wear & weather resistant
- Protects finish from abrasion, water stains and alcohol

## VOC / MIR (sprays)

350 gm/l  
(2.92 lbs/gal)

## NET WEIGHT

8 lbs/gal

## AVAILABLE SIZES

gallon, quart

## SHIPPING WT

4-gal case/33.5 lbs  
4-qt case/9.05 lbs

## AVAILABLE COLORS

8-0310 Clear Gloss, 8-0312 Clear Satin

## SHIPPING RESTRICTION

CA

## PRODUCT STATISTICS

|                                   |  |                                       |                                   |                                   |                           |
|-----------------------------------|--|---------------------------------------|-----------------------------------|-----------------------------------|---------------------------|
| <b>DRYTIME-TOUCH</b><br>2-4 hours | <b>DRYTIME-RECOAT</b><br>12 hours      | <b>WET/ FILM THK</b><br>2.0 mils      | <b>FILM THK /DRY:</b><br>1.0 mils | <b>FINISH</b><br>Gloss Satin      | <b>GLOSS</b><br>80+ @ 60° |
| <b>FLASHPOINT</b><br>> 105° F     | <b>COVERAGE</b><br>Up to 600 sq ft/gal | <b>VISCOSITY</b><br>25 - 35" # 3 Zahn | <b>VEHICLE</b><br>Polyurethane    | <b>SOLVENT</b><br>Mineral Spirits |                           |

## SURFACE PREP

New wood should be sanded thoroughly. Remove all traces of dust with a tack cloth. On previously finished wood, remove any shellac, lacquer or varnish with paint remover. All wax, grease or dust must be removed. Any finish in poor condition must be sanded smooth. Sand surface thoroughly and remove sanding dust with a tack cloth.

## APPLICATION

Apply when surface and air temperatures are 65° F or higher. Stir gently, lifting from the bottom. DO NOT SHAKE. Apply with good quality brush, short nap roller or spray gun, using a minimum number of strokes. Recoat in 12 hours. Sand between coats for smoothest results, especially if more than 12 hours have elapsed between coats. DO NOT THIN.

## WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.