


# Majic Interior Quick Dry, Clear Wood Coating

**8-0362 Series**

## DESCRIPTION

A hard drying crystal-clear finish for interior wood surfaces that dries dust free in 30 minutes and can be handled in one hour. This product is easily applied by brush or spray. It is resistant to toughest wear and is not harmed by alcohol, water or detergents. Majic Quick Dry Varnish is available in a full gloss finish or a satin finish for a rich, hand-rubbed appearance.



## FEATURES

- For interior use only
- Dries dust free in 30 minutes
- Provides a waterproof crystal clear finish
- Provides a durable finish

## VOC / MIR (sprays)

550 gm/l  
(4.60 lbs/gal)

## NET WEIGHT

7.01 lbs/gal

## AVAILABLE SIZES

quart, 1/2 pint

## SHIPPING WT

4-qt case/12 lbs  
6-half pint case/4.8 lbs

## AVAILABLE COLORS

8-0362 Clear Gloss, 8-0363 Clear Satin

## SHIPPING RESTRICTION

CA

## PRODUCT STATISTICS

<b>DRYTIME-TOUCH</b> 1 hour	<b>DRYTIME-RECOAT</b> 24 hours	<b>WET/ FILM THK</b> 3.9 mils	<b>FILM THK /DRY:</b> 1.1 mils	<b>FINISH</b> Gloss Satin	<b>GLOSS</b> 80+ @ 60°
<b>FLASHPOINT</b> 50° F	<b>COVERAGE</b> Approx 500 sq ft/gal	<b>VISCOSITY</b> 35 - 50" Zahn #2	<b>VEHICLE</b> Alkyd	<b>SOLVENT</b> Mineral Spirits	

## SURFACE PREP

The surface should be clean, dry, smoothly sanded and free of dust, grease or wax. Allow freshly applied stain or sealer to dry at least 12 hours before applying Majic Quick Dry Varnish. For an extra smooth finish, apply a first coat of Majic Sanding Sealer following label directions.

## APPLICATION

Stir product thoroughly and gently. DO NOT SHAKE. Majic Quick Dry Varnish should be flowed on with good quality natural bristle brush or spray in liberal even coats. Use a minimum number of brush strokes, brushing from the uncoated into the wet coated portion. Apply additional coats for increased luster and added protection. Allow each coat to dry at least 90 minutes, sand lightly, and remove sanding dust before subsequent coats are applied.

## WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.