


Majic Interior Oil Base Wood Stain

8-0391 Series

DESCRIPTION

This is a premium quality penetrating stain for furniture, floors, cabinets and other interior wood surfaces. Majic Interior Oil Base Wood Stain is formulated with special oils and conditioners that enhance the natural beauty of wood. Majic penetrates deep into the wood, sealing the fibers and hardening the surface with minimal grain raising. This stain is easily applied as a wiping stain for better color control.



FEATURES

- Penetrates and seals
- Absorption control formula ensures consistent rich color
- Low odor

VOC / MIR (sprays)

550 gm/l
(4.60 lbs/gal)

NET WEIGHT

7.07-7.29 lbs/gal

AVAILABLE SIZES

quart, 1/2 pint

SHIPPING WT

4-qt case/8.77 lbs
6-half pint case/5 lbs

AVAILABLE COLORS

8-0391 Dark Walnut, 8-0393 Early American, 8-0395 Golden Oak, 8-0397 Colonial Maple, 8-0398 American Cherry, 8-0399 Red Mahogany

SHIPPING RESTRICTION

None

PRODUCT STATISTICS

| | | | | | |
|---------------------------------------|---|--|------------------------------------|-----------------------------------|---------------------|
| DRYTIME-TOUCH 10-20 minutes | DRYTIME-RECOAT At least 5 hours | WET/ FILM THK 3.1 mils | FILM THK /DRY: 1.0 mils | FINISH n/a | GLOSS n/a |
| FLASHPOINT > 105° F | COVERAGE Up to 126 sq ft/qrt | VISCOSITY 35 - 45 sec, Zahn #1 | VEHICLE Tung/Linseed Oil | SOLVENT Mineral Spirits | |

SURFACE PREP

The surface should be clean and dry, free from dirt, wax and sap residue. Previously painted or varnished surfaces must be stripped down to bare wood. Old stain should be removed completely to achieve a smooth, clean, bare wood surface. Sand all surfaces thoroughly with fine sandpaper. Remove dust with a tack cloth or a rag dampened in mineral spirits.

APPLICATION

The final stain color is affected by the grain structure and species of wood. Stain colors can be intermixed to achieve the desired effect. The stain should be applied at room temperature. Stir with a flat paddle, bringing the pigment from the bottom to the top. Stir frequently during use. Apply with a soft cloth or brush. Allow to penetrate 5 to 15 minutes, removing excess with a clean cloth. If a lighter shade of stain is required, add Majic Natural Wood Stain. For a darker shade apply a second coat of stain. Soft woods may require a second stain coat to provide a more even stain appearance. DO NOT THIN.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.