

Majic Reducer

8-0750

DESCRIPTION

Specially formulated with non-regulated VOC to provide the perfect spray consistency when added to Majic Tractor, Truck & Implement Enamel or Majic Rust Kill Enamel without compromising the VOC limits of these products.



FEATURES

- Provides perfect spray consistency
- Does not compromise VOC limits

VOC / MIR (sprays)

Exempt VOC Formula

NET WEIGHT

1.1 lbs/container

AVAILABLE SIZES

pint

SHIPPING WT

12 pint carton/14 lbs

AVAILABLE COLORS

8-0750 Clear

SHIPPING RESTRICTION

None

PRODUCT STATISTICS

| | | | | | |
|-----------------------------|------------------------------|-----------------------------|------------------------------|-----------------------|---------------------|
| DRYTIME-TOUCH n/a | DRYTIME-RECOAT n/a | WET/ FILM THK n/a | FILM THK /DRY: n/a | FINISH n/a | GLOSS n/a |
| FLASHPOINT -4° F | COVERAGE n/a | VISCOSITY n/a | VEHICLE n/a | SOLVENT n/a | |

SURFACE PREP

All surfaces, new or previously painted, must be clean, dry and free of dust, dirt, grease or mildew. Remove loose, scaling paint by wire brushing, scraping or sanding. Glossy surfaces and all protected areas not exposed to normal weathering should be dulled by sanding. Remove oil residues from new metal surfaces by cleaning with rags saturated in mineral spirits. Surfaces with extensive rust or heavy oxidation should be cleaned to remove loose scale, dust and debris..

APPLICATION

Add one pint of Majic Reducer to one gallon of Majic Tractor Truck & Implement Enamel or Majic Rust Kill Enamel. Stir thoroughly. Use an airless sprayer with a minimum pressure of 2000 PSI with a 60 mesh filter, and tip size of .013 -.017. Conventional spray application may require two pints of Majic Reducer for 40-50 PSI. Check tip for wear after spraying 50 gallons and replace if necessary.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.