

Majic Camouflage Paint

8-0850 Series

DESCRIPTION

Majic camouflage paint offers a flat, non-reflective finish that is rust inhibiting and water resistant to protect wood and metal from the elements. The color selection is perfect for breaking up outlines and shapes with camouflage allowing you to blend with almost any nature background.



FEATURES

- Flat, non-reflective finish
- Water resistant
- Provides camouflage with any nature background
- Perfect for use on vehicles, boats, trailers, duck blinds, free stands, ladders, ladder stands, guns, bows, etc.

VOC / MIR (sprays)

420 gm/l
(3.5 lbs/gal)

NET WEIGHT

3.0 - 3.3 lbs/qt

AVAILABLE SIZES

gallon, quart

SHIPPING WT

2-gal case/22 lbs
4-qt case/11 lbs

AVAILABLE COLORS

8-0850 Olive Drab, 8-0851 Black, 8-0852 Khaki, 8-0853 Bark Gray, 8-0854 Earth Brown, 8-0855 Desert Tan

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 5 - 10 hours	DRYTIME-RECOAT 24 hours	WET/ FILM THK 3 mils	FILM THK /DRY: 1.5 mils	FINISH Flat	GLOSS 0-3 @ 60°
FLASHPOINT 108° F	COVERAGE Approx 450 sq ft/gal	VISCOSITY 90 - 95 KU	VEHICLE Alkyd	SOLVENT Aliphatic	

SURFACE PREP

Bare Metal: Remove all rust scale with wire brush or sander. Remove oil or grease with paint thinner. Prime with rust inhibiting primer.
Painted Metal: Remove loose or peeling paint and rust scale with wire brush or sander. Remove oil or grease with paint thinner. Prime any bare metal with rust inhibiting primer. Painted Surfaces: (General) Make sure surface is clean, dry and free of loose paint, dirt, wax, grease, etc. Sand glossy areas. Spot prime absorbent areas.

APPLICATION

Stir thoroughly. Apply with a high quality brush, roller, paint pad or by spray equipment. Where necessary, apply a second coat and allow each coat to dry thoroughly before applying the next coat. Do not apply if surface temperature is below 50° F (10° C) or in direct sunlight. On unpainted surfaces, sand lightly and apply two coats for best results, sanding lightly between coats.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.