

Rust Kill Multi-Purpose Spray Enamel

8-2001 Series

DESCRIPTION

Rust Kill Oil Base Enamel is a high quality alkyd resin enamel containing a superior, long lasting rust-inhibiting pigment. Rust Kill applies smoothly and dries quickly to a long-lasting weatherproof finish. This enamel dries to a gloss finish that is non-chalking and fade resistant to give maximum beauty and protection on most interior and exterior surfaces.



FEATURES

- Protects metal, wood or masonry
- Superior rust protection
- Fade resistant and non-yellowing
- High hiding

VOC / MIR (sprays)

All <1.20 Except:
2013 <1.90

NET WEIGHT

n/a

AVAILABLE SIZES

12 oz spray

SHIPPING WT

6-12 oz carton/6 lbs

AVAILABLE COLORS

8-2001 Gloss White, 2002 Gloss Black, 2003 Dark Brown, 2004 Sandy Beige, 2005 Orange, 2006 Royal Blue, 2007 Red, 2008 Machine Green, 2009 Light Yellow, 2010 Battleship Gray, 2011 Navy Gray, 2013 Alum, 2014 Red Primer, 2015 Gray Primer, 2016 Matte White, 2017 Matte Black, 2021 SG White, 2022 SG Black, 2048 Charleston Green

SHIPPING RESTRICTION

None

PRODUCT STATISTICS

DRYTIME-TOUCH 9 hours	DRYTIME-RECOAT 24 hours	WET/ FILM THK n/a	FILM THK /DRY: n/a	FINISH Gloss/Matte	GLOSS Varies
FLASHPOINT < 50° F	COVERAGE Up to 26 sq ft/can @ 1 mil	VISCOSITY n/a	VEHICLE Alkyd-Oil	SOLVENT Refer to MSDS	

SURFACE PREP

All Surfaces, new or previously painted, must be clean, dry and free of dust, dirt, grease or mildew. Remove loose scaling paint by wire brushing, scraping or sanding. Glossy surfaces and all protected areas not exposed to normal weathering should be dulled by sanding. Remove oil residues from new metal surfaces by cleaning with rags saturated in mineral spirits. Surfaces with extensive rust or heavy oxidation should be cleaned to remove loose scale, dust and debris. Ferrous Metal: Prime with Rust Kill Primer 8-2014 Red Oxide or 8-2015 Gray. For extra protection, spot prime welded joints and intersections with the primer, then follow with one full primer coat over the entire surface. Rust Metal: Prime with 8-2014 Rust Kill Red Primer. Galvanized Metal: On galvanized metal that is new or in sound condition, apply one coat of a latex galvanized metal primer. On galvanized surfaces that are rusted or in a deteriorated condition, prime with Rust Kill Primer 8-2014 Red or 8-2015 Gray. Wood: Apply a prime coat of an alkyd wood primer or enamel undercoat. Bare Aluminum: Apply one coat of 8-2015 Rust Kill Gray Primer. Masonry Block: Porous surfaces should be filled and sealed, using a vinyl-acrylic or cement based filler. Apply two finish coats of Rust Kill Enamel. Previously Painted Surfaces: Previously painted surfaces in good condition do not require priming. If the surface is in poor condition, prime bare spots as indicated above.

APPLICATION

Always apply paint at room temperature (70°-80° F). To ensure color uniformity and prevent clogging. SHAKE CAN vigorously for at least one minute after mixing ball rattles. Hold can in an upright position 10" to 16" from the object being sprayed. Press spray button with a twisting motion with top of can and spray button opening pointed away from you. Always clean spray button immediately after use by turning can upside down and pressing spray button until no more paint comes out.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.