

# Majic Inverted Marking Spray

**8-20030 Series**

## DESCRIPTION

Majic Inverted Marking Spray adheres to gravel, soil, grass, concrete, and blacktop and withstands general weathering.



## FEATURES

- Makes fast dry, high visibility lines for marking athletic fields, sporting events, landscaping, playgrounds, work sites, lumber and more.

## VOC / MIR (sprays)

<1.20

## NET WEIGHT

n/a

## AVAILABLE SIZES

15 oz spray

## SHIPPING WT

6-15 oz cans/8 lbs

## AVAILABLE COLORS

8-20030 Traffic White, 8-20031 Traffic Yellow, 8-20032 Safety Red, 8-20035 Fluorescent Red, 8-20036 Fluorescent Yellow, 8-20037 Fluorescent Red Orange, 8-20038 Fluorescent Blue, 8-20039 Fluorescent Green

## SHIPPING RESTRICTION

None

## PRODUCT STATISTICS

<b>DRYTIME-TOUCH</b> 1 hour	<b>DRYTIME-RECOAT</b> 8 hours	<b>WET/ FILM THK</b> n/a	<b>FILM THK /DRY:</b> n/a	<b>FINISH</b> Flat	<b>GLOSS</b> < 5 @ 60°
<b>FLASHPOINT</b> < 50° F	<b>COVERAGE</b> Up to 20-30 sq ft/can @ 1 mil	<b>VISCOSITY</b> n/a	<b>VEHICLE</b> Alkyd	<b>SOLVENT</b> Refer to MSDS	

## SURFACE PREP

Cover surrounding areas to protect from spray mist.

## APPLICATION

Shake can for one minute after mixing ball begins to rattle. Shake often during use. Turn upside down and point at ground. Hold can 4-8" above surface to be marked. Press tip sideways and spray steady even strokes to prevent build-up. Use when temperature is between 40° and 90° F and humidity is below 85%. Avoid spraying in windy, dusty conditions. If clogging develops remove spray button with a twisting motion and clean in mineral spirits. DO NOT STICK PIN OR OTHER OBJECT INTO CAN. Gently replace spray button with a twisting motion with top of can and spray button opening pointed away from you. Always clean spray button immediately after use by turning can upright and pressing spray button until no more paint comes out.

## WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.