

# Majic Spray Enamel

**8-20100 Series**

## DESCRIPTION

Perfect for use on indoor and outdoor furniture, bicycles, hobbies and crafts, metal and wood railings, mailboxes, doors and cabinets, signs and tools. Dries fast to a smooth professional finish every time.



## FEATURES

- Dries in 30 minutes or less
- Provides a smooth, durable finish
- Use on metal & wrought iron, wood, wicker, plastics & rubber, plaster & ceramics, masonry, and paper products

## VOC / MIR (sprays)

All <1.40 Except:  
20102, 20121, 20140, 20141  
<1.20

## NET WEIGHT

n/a

## AVAILABLE SIZES

9 oz spray

## SHIPPING WT

6-9 oz carton/6 lbs

## AVAILABLE COLORS

8-20100 Gloss White, 20102 Matte White, 20103 Yellow, 20109 Red, 20110 Royal Blue, 20111 Hunter Green, 20112 Brown, 20114 Machinery Gray, 20120 Gloss Black, 20121 Matte Black, 20140 Gray Primer, 20141 Red Oxide Primer, 20148 Almond

## SHIPPING RESTRICTION

None

## PRODUCT STATISTICS

<b>DRYTIME-TOUCH</b> 2 hours	<b>DRYTIME-RECOAT</b> 8 hours	<b>WET/ FILM THK</b> n/a	<b>FILM THK /DRY:</b> n/a	<b>FINISH</b> Gloss	<b>GLOSS</b> 70+ @ 60°
<b>FLASHPOINT</b> < 50° F	<b>COVERAGE</b> Up to 15 sq ft/can @ 1 mil	<b>VISCOSITY</b> n/a	<b>VEHICLE</b> Alkyd	<b>SOLVENT</b> Refer to MSDS	

## SURFACE PREP

Remove visible rust on metal with a wire brush, sandpaper or scraper. Sand metal, wood or plastic with 220 grit sandpaper. Clean to remove grease, oil and dirt. Allow to dry thoroughly, then wipe with a tack cloth. Use a primer on new wood and on new or rusted metal to smooth uneven surfaces, or when dramatically changing color. Allow primer to dry for 8 hours before lightly sanding and top coating with Majic Spray Paint.

## APPLICATION

Shake can for 2 minutes after enclosed ball begins to rattle. Repeat for 10 seconds after each minute of use. Test spray on an inconspicuous area for substrate compatibility. Spray 10-12" from surface in a sweeping motion maintaining a consistent distance from the item being painted. Apply in thin coats to avoid runs or drips. Do not apply in one continuous spray. Release the spray button after each pass. Clean valve by holding can upside down and spraying until only clear gas is released. If spray valve becomes clogged, pull spray button off and clean it in lacquer thinner. Do not stick pins or wire into can opening. Replace spray button with valve opening pointing away from body. Replace cap for future use. Remove over spray with paint thinner. Clean hands with lacquer or paint thinner, then wash thoroughly with soap and water.

## WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.