

# Majic Polyurethane Wood Coating Clear Spray

**8-20300 Series**

## DESCRIPTION

A hard protective finish which offers long lasting beauty. This product provides a finish that is resistant to water, chemicals, detergents, alcohol, impact and abrasion. Formulated and recommended for application on bare wood to seal the wood and to provide a coating that can be sanded to create a smooth surface.



## FEATURES

- Wear & weather resistant
- Hard protective finish
- Enriches the natural beauty of the wood
- Protects finish from abrasion, water, alcohol, cleaners and stains

## VOC / MIR (sprays)

<1.50

## NET WEIGHT

n/a

## AVAILABLE SIZES

11 oz spray

## SHIPPING WT

6-11 oz carton/6 lbs

## AVAILABLE COLORS

8-20300 Clear Gloss, 8-20386 Clear Satin

## SHIPPING RESTRICTION

None

## PRODUCT STATISTICS

<b>DRYTIME-TOUCH</b> 10 hours	<b>DRYTIME-RECOAT</b> 12 hours	<b>WET/ FILM THK</b> n/a	<b>FILM THK /DRY:</b> n/a	<b>FINISH</b> Gloss/Satin	<b>GLOSS</b> 80+ @ 60° 18-25 @ 60°
<b>FLASHPOINT</b> < 50° F	<b>COVERAGE</b> Up to 24 sq ft/can @ 1 mil	<b>VISCOSITY</b> n/a	<b>VEHICLE</b> Alkyd	<b>SOLVENT</b> Refer to MSDS	

## SURFACE PREP

New wood should be sanded thoroughly. Remove all traces of dust with a tack cloth. On previously finished wood, remove any shellac, lacquer or varnish with paint remover. All wax, grease or dust must be removed. Any finish in poor condition must be sanded smooth. Sand surface thoroughly and remove sanding dust with a tack cloth.

## APPLICATION

Always apply paint at room temperature (70° to 80° F). To ensure color uniformity and prevent clogging. SHAKE CAN vigorously for at least one minute after mixing ball rattles. Hold can in an upright position 10" to 16" from the object being sprayed. Press spray button with a twisting motion with top of can and spray button opening pointed away from you. Always clean spray button immediately after use by turning can upside down and pressing spray button until no more paint comes out.

## WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.