

Majic Town & Country Tractor, Truck & Implement Spray Enamel

8-20951 Series

DESCRIPTION

Majic Tractor, Truck & Implement Spray Enamel is a durable, heavy-duty alkyd enamel specially formulated for excellent adhesion, and resistance to weathering and corrosion. It dries quickly to a high gloss finish. Use it on iron, steel, aluminum and properly primed galvanized metal.



FEATURES

- Use on equipment, implements, tools, etc. where a hard enamel finish is desired
- Special heavy-duty alkyd formula
- Excellent adhesion
- Authorized by USDA for use in federally inspected meat and poultry plants
- Colors match Tractor Truck & Implement Enamel in gallon and quart containers.

VOC / MIR (sprays)

<1.20

AVAILABLE SIZES

11 oz spray

NET WEIGHT

n/a

SHIPPING WT

6-11 oz carton/6 lbs

AVAILABLE COLORS

8-20951 IH Wht, 20952 NH Yel, 20953 Rustic Brw, 20954 Frd Red, 20955 MF Gray, 20956 NH Red, 20957 New JD Yel, 20958 Case Orange, 20959 Matte Blk, 20960 Morra Red, 20961 MF Red, 20962 Cat Yel, 20964 JD Yel, 20965 AC Orange, 20966 JD Green, 20967 Lt Ford Gray, 20968 Frd Blue, 20971 Kubota Orange, 20972 IH Red, 20973 Sch Bus Yel, 20974 Oliver Green, 20979 New Frd/NH Blue, 20983 Case Pwr Yel, 20984 Alum, 20990 Gls Wht, 20994 Gls Blk

SHIPPING RESTRICTION

None

PRODUCT STATISTICS

| | | | | | |
|---------------------------------|---|-----------------------------|------------------------------|---------------------------------|---------------------------|
| DRYTIME-TOUCH 6 hours | DRYTIME-RECOAT 24 hours | WET/ FILM THK n/a | FILM THK /DRY: n/a | FINISH Gloss/Matte | GLOSS 80+ @ 60° |
| FLASHPOINT < 50° F | COVERAGE Up to 27 sq ft/can @ 1 mil | VISCOSITY n/a | VEHICLE Alkyd | SOLVENT Refer to MSDS | |

SURFACE PREP

Bare Metal: Remove all rust scale with wire brush or sander. Remove oil or grease with paint thinner. Prime with rust-inhibiting primer 8-20986 Gray Primer or 8-20989 Red Oxide Primer. Painted Metal: Remove loose or peeling paint and rust scale with wire brush or sander. Remove oil or grease with paint thinner. Prime any bare metal with rust-inhibiting primer. Painted Surfaces: (General) Make sure surface is clean, dry and free of loose paint, dirt, wax, grease, etc. Sand glossy areas. Spot prime absorbent areas.

APPLICATION

Protect surrounding surface with drop cloths. Always apply paint at room temperature (70°-80° F). to ensure color uniformity and prevent clogging. SHAKE CAN vigorously for at least one minute after mixing ball rattles. Hold can in an upright position 10" to 16" from the object being sprayed. Press spray button firmly. Use steady, even strokes while spraying. Several thin coats will result in a better finish than one heavy coat. If clogging develops remove spray button with a twisting motion and clean button with a twisting motion with top of can and spray button opening pointed away from you. Always clean spray button immediately after use by turning can upside down and pressing spray button until no more paint comes out.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.