

Town & Country Rust Preventative Sandable Primer Spray

8-20987

DESCRIPTION

Town & Country Rust Preventative Sandable Primer Spray provides a tough, rust-inhibitive base. Sprays and sands smooth for the ultimate finish.



FEATURES

- Sprays and sands smooth for the ultimate finish

VOC / MIR (sprays)

<1.20

NET WEIGHT

n/a

AVAILABLE SIZES

10 oz spray

SHIPPING WT

6-10 oz carton/5 lbs

AVAILABLE COLORS

8-20987 Gray

SHIPPING RESTRICTION

None

PRODUCT STATISTICS

DRYTIME-TOUCH 1 hour	DRYTIME-RECOAT 4 hours	WET/ FILM THK n/a	FILM THK /DRY: n/a	FINISH Flat	GLOSS 0-10 @ 60°
FLASHPOINT < 50° F	COVERAGE 5 sq ft/can	VISCOSITY n/a	VEHICLE Alkyd	SOLVENT Refer to MSDS	

SURFACE PREP

Surface must be dry and free of dirt, dust, grease or wax. Protect surrounding areas with drop cloths.

APPLICATION

Always apply at room temperature (70° - 80° F). To ensure color uniformity and prevent clogging, SHAKE CAN vigorously for at least one minute after mixing ball rattles. Hold can in an upright position 10" to 16" from the object being sprayed. Press spray button firmly. Use steady even strokes while spraying. Several thin coats will result in a better finish than one heavy coat. If clogging develops remove spray button with a twisting motion and clean in mineral spirits. DO NOT STICK PIN OR OTHER OBJECT INTO CAN. Gently replace spray button with a twisting motion with top of can and spray button opening pointed away from you. Always clean spray button immediately after use by turning can upside down and pressing spray button until no more paint comes out.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.