

Town & Country Latex Satin for Barns, Homes and Fences

8-7773 Series

DESCRIPTION

Majic Premium Town & Country Latex Satin Paint is a premium quality latex paint modified with linseed oil for good penetration and adhesion to new or weathered wood. It resists fading and dries to a non-toxic film that is safe for use around livestock.



FEATURES

- Linseed oil fortified
- Self priming
- Fade resistant
- Weather resistant
- Soap and water cleanup

VOC / MIR (sprays)

150 gm/l
(1.25 lbs/gal)

NET WEIGHT

9.25 lbs/gal

AVAILABLE SIZES

5-gallon, gallon

SHIPPING WT

5-gal pail/53 lbs
4-gal case/43 lbs

AVAILABLE COLORS

8-7773 Classic Red, 8-7774 White, 8-7775 Bright Red

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 1 hour	DRYTIME-RECOAT 8 hours	WET/ FILM THK 4.5 mils	FILM THK /DRY: 1.0 mil	FINISH Satin	GLOSS 15-25 @ 60°
FLASHPOINT > 200° F	COVERAGE Up to 300 sq ft/gal	VISCOSITY 90 - 95 KU	VEHICLE Vinyl Acrylic/Acrylic Emulsion	SOLVENT Water	

SURFACE PREP

Previously Painted Wood: Scrape to remove loose, peeling paint and sand smooth. Remove all loose dirt and chalk. Scrub protected areas under eaves to remove invisible deposits which cause peeling. Remove any mildew using one quart of household bleach in three quarts of water. Rinse thoroughly and let dry completely. Wear goggles and gloves to prevent contact with the bleach. Sand any glossy areas to dull the surface. Caulk cracks and putty nail holes. Spot prime any bare areas with appropriate exterior primer. Previously Painted Masonry: Removes loose or powdery paint and chalk. Spot prime bare areas with this product. Metal Surfaces: Scrape or wire brush to remove rust and loose paint. Spot prime bare metal with the proper metal primer. New Unpainted Surfaces: Wood Siding & Trim-Caulk cracks and joints, putty nail holes. Prime with an alkyd or latex exterior primer. Masonry-Newly poured concrete must be weathered a minimum of 90 days. Remove chalk and dirt by washing and rinse thoroughly. You may observe white stains or deposits on the Masonry. This is known as efflorescent salts and must be removed with a solution of muriatic acid and water. Rinse thoroughly and let dry completely. Wear goggles and gloves to prevent contact with the muriatic acid.

APPLICATION

Stir thoroughly. If you are using two or more gallons of the same color, mix together and stir paint thoroughly to make sure color is uniform. Apply generously with a nylon or polyester brush or good quality roller. Stop painting at least four hours before nightfall, stopping at the end of a wall or corner. Do not paint when temperatures are below 50° F, in direct sunlight, or if rain is expected in the next 24 hours. On hot days, surface may be dampened with water to slow drying. DO NOT THIN.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.