

Majic Barricade Primer & Sealer

8-0068

DESCRIPTION

Majic Barricade Quick Dry, Oil Base Primer Sealer is a fast drying primer and stain blocker. This product will block out a variety of difficult stains including water, graffiti, rust, smoke, and crayon. Use it on drywall, plaster, wood, or metal. It is suitable for previously painted or new work, adheres to most glossy surfaces and should be top coated with any latex or oil base paint. Majic Barricade Quick Dry Primer Sealer is not recommended over solvent sensitive stains such as asphalt or tar.



FEATURES

- Retards bleeding from water, smoke, grease and more!
- Seals interior drywall, plaster and wood
- Use under alkyd or latex finish coats
- Meets all government VOC regulations

VOC / MIR (sprays)

350 gm/l
(2.92 lbs/gal)

NET WEIGHT

12.30 lbs/gal

AVAILABLE SIZES

gallon, quart

SHIPPING WT

4-gal case/55 lbs
4-qrt case/14 lbs

AVAILABLE COLORS

8-0068 White

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 2 hrs for finish coat	DRYTIME-RECOAT 2 hrs to sand	WET/ FILM THK 3.0 mils	FILM THK /DRY: 1.5 mils	FINISH Flat	GLOSS 2-5 @ 60°
FLASHPOINT 50° F	COVERAGE Up to 400 sq ft/gal.	VISCOSITY 70 - 75 KU	VEHICLE Alkyd-Oil	SOLVENT Mineral Spirits	

SURFACE PREP

The surface must be dry and free of peeling paint, loose rust, excessive chalk, wax or mildew. Remove loose wallpaper and wallpaper paste. Fill cracks and nail holes with patching compound and sand smooth. This product is an ideal primer over most glossy surfaces, but should be tested for good adhesion before proceeding. Paint a small area and wait 24 hours. Place masking tape on the test area and remove the tape. If the tape lifts the primer, sand the surface lightly or use deglosser before using this product.

APPLICATION

Stir the paint thoroughly. Apply with brush, roller or spray. When brushing, best results are obtained with a good bristle brush. If rolling, use a short nap roller for best appearance. Do not apply too heavily. A good even coat will assure effective stain kill. This product comes ready to use and should not be thinned. After sealing stained areas with this product, test a small section with application of the finish coat. If the stain bleeds through, apply a second coat of Majic Barricade Quick Dry Primer Sealer and re-test. Do not apply if temperature is below 50° F. This product must be used with good ventilation. Avoid prolonged breathing of the vapors.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.