

Majic Floor Enamel

8-0175

DESCRIPTION

Uniform high hiding finish for interior and exterior wood, concrete and primed metal that provides beautiful, trouble free protection against weather.



FEATURES

- Designed to produce durable finish in light commercial and residential application
- Will withstand detergents, oils, grease and scrubbing.

VOC / MIR (sprays)

250 gm/l
(2.10 lbs/gal)

NET WEIGHT

9.7 lbs/gal

AVAILABLE SIZES

gallon

SHIPPING WT

4-gal case/43 lbs

AVAILABLE COLORS

8-0175 Battleship Gray

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 2 hours	DRYTIME-RECOAT 8 hours	WET/ FILM THK 4.5 mils	FILM THK /DRY: 1.0 mils	FINISH Satin	GLOSS 8-15 @ 60°
FLASHPOINT > 200° F	COVERAGE Up to 300 sq ft/gal	VISCOSITY 90 - 95 KU	VEHICLE Vinyl Acrylic Latex	SOLVENT Water	

SURFACE PREP

Be sure the surface is sanded smooth and free of dirt and dust. Prime with latex wood primer. Previously Painted Wood: Remove any loose paint, dirt, grease, or wax from the surface. Spot prime bare wood areas with Majic Floor Enamel. Sand glossy areas. New Concrete: Allow the freshly poured concrete to age at least 90 days before painting. For best results, smoothly troweled surfaces should be etched with a solution of 1 part muriatic acid to 3 parts water then rinsed thoroughly. Wear goggles and gloves to prevent contact with the acid. Previously Painted Concrete: Remove all loose paint, dirt, grease or wax. Cleaning is best accomplished using a strong solution of trisodium phosphate. Wear goggles and gloves to prevent contact with the trisodium phosphate. Rinse thoroughly, sweeping water with a broom. Spot prime bare areas with Majic Floor Enamel.

APPLICATION

Do not paint at surface temperatures below 50° F. Stir the paint thoroughly until uniform. Apply generously using a good quality nylon brush or short nap roller. On unpainted wood, two coats will be needed over the primer to seal the surface completely. Allow 8 hours drying between coats. Paint may be applied to slightly damp surfaces but should not be applied during or within 12 hours of expected rain. Painted surfaces may be walked on after drying overnight. Textured surfaces or extreme color changes may require a second application. When using two or more gallons of the same color, mix paint together to assure uniform color. DO NOT THIN.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.