

Barricade Primer & Paint

8-1091

DESCRIPTION

This is a quality finish that features good coverage when sprayed or rolled. It is ideal for general maintenance and "cleanup" of wallboard surfaces. It will provide a two coat system on new drywall.



FEATURES

- Covers up to 30 sheet of drywall
- Perfect for drywall, plaster & textured surfaces

VOC / MIR (sprays)

100 gm/l
(0.83 lbs/gal)

NET WEIGHT

10.15 lbs/gal

AVAILABLE SIZES

5-gallon, gallon

SHIPPING WT

5-gal pail/53 lbs
4-gal case/43 lbs

AVAILABLE COLORS

8-1091 White, 8-1092-5 Oyster White

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 1 hour	DRYTIME-RECOAT 4 hours	WET/ FILM THK 6.0 mils	FILM THK /DRY: 1.0 mil	FINISH Flat	GLOSS 2-5 @ 60°
FLASHPOINT > 200° F	COVERAGE Up to 300 sq ft/gal	VISCOSITY 90 - 105 KU	VEHICLE Vinyl Acrylic Latex	SOLVENT Water	

SURFACE PREP

The surface to be painted must be clean & free of dirt, wax, oil, grease, paste, and water soluble residue. If washing the surface is necessary, use a water based, low sudsing detergent and rinse well with clean water. Remove any mildew using one quart of household bleach in 3 quarts of water. Rinse thoroughly. Wear goggles and gloves to prevent contact with the bleach. Loose and scaling paint should be removed by scraping or sanding. Repair holds, crevices and cracks with spackling compound, and sand smooth. Dull glossy areas with sandpaper or surface prep agent. If using a liquid deglosser or primer, follow the directions closely and test a small area for compatibility with the finish coat. Stains from water, smoke, ink and crayon will bleed through most paint. Cover these areas with a stain blocking primer. Satisfactory results can be obtained on most wallboard surfaces with two coats of this product. Some types of wallboard and joint compound, however, require a good latex primer sealer for best appearance.

APPLICATION

Do not paint at temperatures below 50° F. Stir the paint thoroughly. Apply generously with a good quality nylon or polyester brush or medium nap roller. First paint a 2 to 3 inch strip at the ceiling and baseboard, around windows and doors, and in corners with a sash brush. Overlap these brushed areas as much as possible maintaining a wet edge as you continue painting with the roller. Do not spread paint too far. One roller-full should cover an area approximately 3' x 3'. Use a 3/8" to 1/2" nap roller for large areas. For airless spray application, use a .013 to .015 reversible tip at 700 to 1,200 PSI. This paint may be thinned with up to 1/2 pint water per gallon for the first coat. Do not thin the finish coat or when doing one coat work. Do not subject the finish to washing for at least 30 days. Textured surfaces or extreme color changes may require an additional coat. DO NOT THIN.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.