

# Diamondhard Kidproof Ceramic Velvet Matte Wall Paint

**8-1700 Series**

## DESCRIPTION

Kidproof Ceramic Velvet Matte Wall Paint has ceramic bead technology which combines a designer matte wall finish and a scrubbable, stain resistant surface to give you the best coating possible for any high traffic area.



## FEATURES

- Ceramic Bead Technology provides a stain release, scrubbable finish
- Perfect for use on drywall, masonry, and primed wood and metal
- Soap & water clean up
- Friendly to the environment - No hazardous air pollutants.
- Made with soy products and recycled materials

## VOC / MIR (sprays)

50 gms/l  
(.42 lbs/gal)

## NET WEIGHT

10.74 lbs/gal

## AVAILABLE SIZES

gallon

## SHIPPING WT

4-gal case/45 lbs

## AVAILABLE COLORS

8-1700 High Hiding White, 8-1720 White T B #1, 8-1721 Midtone T B #2, 8-1722 Deep T B #3, 8-1723 Neutral T B #4

## SHIPPING RESTRICTION

None

## PRODUCT STATISTICS

<b>DRYTIME-TOUCH</b> 1 hour	<b>DRYTIME-RECOAT</b> 4 hours	<b>WET/ FILM THK</b> 3 mils	<b>FILM THK /DRY:</b> 1 mil	<b>FINISH</b> Matte	<b>GLOSS</b> 6-10 @ 60°
<b>FLASHPOINT</b> 200° F	<b>COVERAGE</b> Up to 350 sq ft/gal	<b>VISCOSITY</b> 90 - 95 KU	<b>VEHICLE</b> Vinyl Acrylic	<b>SOLVENT</b> Water	

## SURFACE PREP

Use it on drywall, masonry, and primed wood or metal. The surface to be painted must be clean and free of dirt, wax, oil, grease, paste and water soluble residue. If washing the surface is necessary, use a water based, low sudsing detergent, rinse well with clean water and let dry thoroughly. Remove any mildew using one quart of household bleach in three quarts of water. Rinse thoroughly and let dry completely. Wear goggles and gloves to prevent contact with the bleach. Loose and scaling paint should be removed by scraping or sanding. Repair holes, crevices and cracks with spackling compound and sand smooth. Dull glossy areas with sandpaper or surface prep agent. If using a liquid deglosser or primer, follow the directions closely and test a small area for compatibility with the finish coat. Stains from water, smoke, ink and crayon will bleed through most paint. Cover these areas with an alcohol base or alkyd stain blocking primer. Some types of wallboard and joint compound require a good latex primer sealer for best appearance. Satisfactory results can be obtained on most wallboard surfaces with two coats of this product.

## APPLICATION

Do not paint at temperatures below 50° F. Stir the paint thoroughly. Apply generously with a good quality nylon or polyester brush or medium nap roller. First paint a 2 to 3 inch strip at the ceiling and baseboard, around windows and doors, and in corners with a sash brush. Overlap these brushed areas as much as possible as you continue painting with the roller. Do not spread paint too far. One roller-full should cover an area approximately 3' x 3'. Use a 3/8" to 1/2" nap roller for large areas. Do not subject the finish to washing for at least 30 days. Textured surfaces or extreme color changes may require a second application. When using two or more gallons of the same color, mix paint together to assure uniform color. DO NOT THIN.

## WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.