

# Easy Spread Interior Latex Drywall Primer

**8-1090**

## DESCRIPTION

This is a latex base primer that seals unpainted surfaces providing a base for latex or oil base finish coats. It dries quickly and is ready for recoating in just a few hours. It will not raise the nap on wallboard and prevents flashing or hot spots from appearing in the finish coat. It applies easily with brush, roller or spray. USE IT ON: Drywall, masonry, and wood.



## FEATURES

- Dries quickly
- Promotes adhesion
- For use under oil or latex paint
- Easy to apply

## VOC / MIR (sprays)

100 gm/l  
(0.83 lbs/gal)

## NET WEIGHT

22.16 lbs/2 gal pail

## AVAILABLE SIZES

5-gallon, 2-gallon,  
gallon

## SHIPPING WT

5-gal pail/60 lbs  
2-gal pail/22 lbs  
4-gal case/45 lbs

## AVAILABLE COLORS

8-1090 White

## SHIPPING RESTRICTION

None

## PRODUCT STATISTICS

<b>DRYTIME-TOUCH</b> 1 hour	<b>DRYTIME-RECOAT</b> 2 - 4 hours	<b>WET/ FILM THK</b> 4.5 mils	<b>FILM THK /DRY:</b> 1.0 mils	<b>FINISH</b> Flat	<b>GLOSS</b> 2-5 @ 60°
<b>FLASHPOINT</b> > 200° F	<b>COVERAGE</b> Up to 300 sq ft/gal	<b>VISCOSITY</b> 95 - 105 KU	<b>VEHICLE</b> Vinyl Acrylic Latex	<b>SOLVENT</b> Water	

## SURFACE PREP

The surface to be painted must be clean and free of dirt wax, oil, grease, paste and water soluble residue. If washing the surface is necessary, use a water based, low sudsing detergent and rinse well with clean water. Let dry thoroughly. Remove any mildew using one quart of household bleach in three quarts of water. Rinse thoroughly and let dry. Wear goggles and gloves to prevent contact with the bleach. Loose and scaling paint should be removed by scraping or sanding. Repair holes, crevices and cracks with spackling compound, and sand smooth. Dull glossy areas with sandpaper or surface prep agent. Stains from water, smoke, ink and crayon should be covered with an alcohol base or alkyd stain blocking primer.

## APPLICATION

Do not paint at temperatures below 50° F. Stir the paint thoroughly. Apply generously with a good quality nylon or polyester brush or medium nap roller. First paint a 2 to 3 inch strip at the ceiling and baseboard, around windows and doors, and in corners with a sash brush. Overlap these brushed areas as much as possible as you continue painting with the roller. Do not spread paint too far. One roller-full should cover an area approximately 3' x 3'. Use a 3/8" to 1/2" nap roller for large areas. To minimize "joint banding" in semi-gloss and gloss finishes, apply a first coat of primer over the tape joints followed by one full primer coat over the entire job. DO NOT THIN.

## WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.