

Easy Spread Exterior Latex Flat Primer

8-2090

DESCRIPTION

A specially formulated undercoat for use on wood, masonry, brick and metal. Easy Spread Exterior Latex Flat Primer provides an excellent base for latex, acrylic and alkyd house paints. This product provides the important first step for a long lasting paint system that is blister and peel resistant.



FEATURES

- Provides an excellent base coat for latex, acrylic, and alkyd finish coats
- Applies easily
- Tools rinse clean in soapy water

VOC / MIR (sprays)

100 gm/l
(0.83 lbs/gal)

NET WEIGHT

10.39 lbs/gal

AVAILABLE SIZES

2-gallon, gallon

SHIPPING WT

2-gal pail/20 lbs
4-gal case/45 lbs

AVAILABLE COLORS

8-2090 White

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 1-2 hours	DRYTIME-RECOAT 8 hours	WET/ FILM THK 4 mils	FILM THK /DRY: 1.3 mils	FINISH Flat	GLOSS 2-8 @ 60°
FLASHPOINT > 200°F	COVERAGE Up to 400 sq ft/gal	VISCOSITY 80 - 85 KU	VEHICLE Vinyl/Acrylic Latex/Alkyd	SOLVENT Water	

SURFACE PREP

The surface must be dry and free of peeling paint, loose rust, excessive chalk, wax or mildew. Fill cracks and nail holes with patching compound and sand smooth. Spot prime knots and rusty nail heads with a shellac type primer to prevent bleed through. Sand scraped areas to promote a more even finish. Sand glossy areas. Thoroughly wash the surface with detergent and water, remove dirt, sanding dust, chalk and pollutants. Remove any mildew using one quart of household bleach in three quarts of water. Rinse and let dry thoroughly. Wear goggles and gloves to prevent contact with the bleach. Allow washed areas to dry at least 48 hours before applying this primer. NOTE: Caulking, puttying and glazing are best done after Easy Spread Exterior Latex Primer has been applied and allowed to dry completely.

APPLICATION

Stir paint thoroughly until uniform. Apply with a good quality brush or roller making sure to get this primer on all exposed surfaces. Do not paint if the surface temperature is below 50°F or if rain is expected within 24 hours. DO NOT THIN.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

REVISED DATE 5/5/2014