

Easy Spread Exterior Latex Semi-Gloss House Paint

8-2300 Series

DESCRIPTION

A semi-gloss house paint formulated to provide a quality finish for your exterior house and trim.



FEATURES

- Applies easily
- Tools rinse clean in soapy water
- For wood and masonry
- Resists blistering and peeling

VOC / MIR (sprays)

50 gm/l

NET WEIGHT

9.4 lbs/gal

AVAILABLE SIZES

5-gallon, gallon

SHIPPING WT

5-gal pail/60 lbs
4-gal case/45 lbs

AVAILABLE COLORS

8-2300 White, 8-2320 Black, 8-2331 Bark Brown, 8-2344 Colonial Red

SHIPPING RESTRICTION

CA

PRODUCT STATISTICS

DRYTIME-TOUCH 1 hour	DRYTIME-RECOAT 8 hours	WET/ FILM THK 4.5 mils	FILM THK /DRY: 1.0 mils	FINISH Semi-Gloss	GLOSS 25-35 @ 60°
FLASHPOINT < 50°F	COVERAGE Up to 300 sq ft /gal	VISCOSITY 88 - 92 KU	VEHICLE Vinyl Acrylic Latex	SOLVENT Water	

SURFACE PREP

Previously Painted Wood: Scrape to remove loose, peeling paint and sand smooth. Remove all loose dirt and chalk. Scrub protected areas under eaves to remove invisible deposits which cause peeling. Remove any mildew using one quart of household bleach in three quarts of water. Rinse thoroughly. Wear goggles and gloves to prevent contact with the bleach. Sand any glossy areas to dull the surface. Caulk cracks and putty nail holes. Spot prime any bare areas with oil base exterior primer. Previously Painted Masonry: Remove loose or powdery paint and chalk. Spot prime bare areas with this product. Metal Surfaces: Scrape or wire brush to remove rust and loose paint. Spot prime bare metal with the proper metal primer. New, Unpainted Surfaces: Wood Siding & Trim: Caulk cracks and joints, putty nail holes. Prime with an alkyd or acrylic latex exterior primer. Masonry: Newly poured Concrete must be weathered a minimum of 90 days. Concrete block should be given two coats of Easy Spread Exterior Latex Semi-Gloss. Galvanized Metal: Check for stabilizing film, remove appropriately and prime with latex galvanized primer. Ferrous Metal: Prime with a red oxide rust inhibiting primer. Bare Aluminum: Prime with an acrylic latex primer.

APPLICATION

Stir thoroughly. Apply generously with nylon or polyester brush or good quality roller. Stop painting at least four hours before nightfall, stopping at the end of a wall or corner. Do not paint when temperatures are below 50°F. in direct sun light, or if rain is expected in the next 24 hours. On hot days surface may be dampened with water to slow drying. DO NOT THIN.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

REVISED DATE 5/5/2014