

Professional Interior PVA Drywall Primer Sealer

8-8780

DESCRIPTION

This is a quick drying, water base primer for interior drywall, acoustical tile and masonry. Professional Interior PVA Primer Sealer seals wallboard and joint compound, providing excellent holdout for application of the finish coat. This primer provides an ideal base for latex and alkyd enamels, as well as epoxy coatings. Use this primer to insure a smooth finish and even sheen from the finish coat.



FEATURES

- High build formula
- Applies easily
- Seals wallboard and joint compound
- Insures a smooth finish and even sheen from the finish coat
- Spatter resistant
- Soap & water clean-up

VOC / MIR (sprays)

100 gm/l
(0.83 lbs/gal)

NET WEIGHT

10.45 lbs/gal

AVAILABLE SIZES

5-gallon, gallon

SHIPPING WT

5-gal pail/57.6 lbs
4-gal case/47 lbs

AVAILABLE COLORS

8-8780 White

SHIPPING RESTRICTION

None

PRODUCT STATISTICS

DRYTIME-TOUCH 30 minutes	DRYTIME-RECOAT 2 - 4 hours	WET/ FILM THK 2.9 mils	FILM THK /DRY: 1.0 mils	FINISH Flat	GLOSS 1-5 @ 60°
FLASHPOINT > 200°F	COVERAGE Up to 350 sq ft/gal	VISCOSITY 93-98 KU	VEHICLE Vinyl Acrylic Latex	SOLVENT Water	

SURFACE PREP

The surface to be painted must be clean and free of dirt, wax, oil, grease, paste and water soluble residue. If washing the surface is necessary, use a water based, low sudsing detergent and rinse well with clean water and let dry. Remove any mildew using one quart of household bleach in three quarts of water. Rinse thoroughly and let dry completely. Wear goggles and gloves to prevent contact with the bleach. Loose and scaling paint should be removed by scraping or sanding. Repair holes, crevices and cracks with spackling compound, and sand smooth. Dull glossy areas with sandpaper or surface prep agent. If using a liquid deglosser or primer, follow the directions closely and test a small area for compatibility with the finish coat. Stains from water, smoke, ink and crayon will bleed through most paint. Cover these areas with an alcohol base or alkyd stain blocking primer.

APPLICATION

Do not paint at temperatures below 50° F. Stir the paint thoroughly. Apply generously with a good quality nylon or polyester brush or medium nap roller. First paint a 2 to 3 inch strip at the ceiling and baseboard, around windows and doors, and in corners with sash brush. Overlap these brushed areas as much as possible as you continue painting with the roller. Do not spread too far. One roller-full should cover an area approximately 3' x 3'. Use a 3/8" to 1/2" nap roller for large areas. For airless spray application, use a .018 reversible tip at 1,500 to 2,000 PSI. Do not thin. Thinning will reduce the sealing and hold-our properties of this product. To minimize "joint banding" in semi-gloss and gloss finishes, apply a first coat of primer over the tape joints followed by one full primer coat over the entire job.

WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

REVISED DATE 4/3/2014