

# Pride 100% Acrylic Latex Lo-Lustre House Paint

8-3401 Series

## DESCRIPTION

Our finest exterior acrylic latex lo-lustre house paint resist blistering, peeling and chalking. It has a weather resistant lo-lustre finish, one coat coverage, and exclusive adhesion properties. This product is designed for use on wood and aluminum siding, masonry, brick, cement block, asbestos shingles, wood trim and metal.



## FEATURES

- 100% Acrylic for maximum durability and washability
- Resists peeling, blistering and chalking
- Ideal for aluminum siding
- Protects the surface from weather
- Can be applied when air temps are as low as 45° F

## VOC / MIR (sprays)

100 gm/l  
(0.83 lbs/gal)

## NET WEIGHT

10.59 lbs/gal

## AVAILABLE SIZES

5-gallon, gallon

## SHIPPING WT

5-gal pail/60 lbs  
4-gal case/45 lbs

## AVAILABLE COLORS

8-3401 High Hiding White, 8-3410 Brilliant White, 8-3481 White TB #1, 8-3482 Midtone TB #2, 8-3483 Deep TB #3, 8-3484 Neutral TB #4

## SHIPPING RESTRICTION

CA

## PRODUCT STATISTICS

<b>DRYTIME-TOUCH</b> 1/2 to 1 hour	<b>DRYTIME-RECOAT</b> 8 hours	<b>WET/ FILM THK</b> 3.0 mils	<b>FILM THK /DRY:</b> 1.0 mils	<b>FINISH</b> Lo-Lustre	<b>GLOSS</b> 5-9 @ 60°
<b>FLASHPOINT</b> > 200°F	<b>COVERAGE</b> Up to 400 sq ft/gal	<b>VISCOSITY</b> 90 - 95 KU	<b>VEHICLE</b> Acrylic Latex	<b>SOLVENT</b> Water	

## SURFACE PREP

New Wood: Prime with an alkyd exterior primer or acrylic primer. Allow 24 hours drying time. Putty nail holes and caulk all cracks and open seams. Cedar or Redwood may require two primer coats to prevent bleed through. Previously Painted Wood: Remove all loose or peeling paint with scraper or sander. Remove any mildew with a solution of trisodium phosphate, bleach and water. Rinse thoroughly and let dry. Wear goggles and gloves to prevent contact with the trisodium phosphate and bleach. Sand all glossy areas. Wash and rinse to remove dirt and chalk. Let dry completely. Spot prime bare areas with and exterior primer. Replace all brittle or cracked caulking. Previously Painted Masonry: Remove all loose or powdery paint and caulk. Spot prime bare areas with this product. New Masonry: Apply two coats of this product. Newly poured concrete should weather for 90 days and be etched with a 10% muriatic acid solution if it is smooth. Wear goggles and gloves to prevent contact with the muriatic acid. Metal Surfaces: Prime iron or steel with a metal primer. Prime unprotected galvanized metal with an acrylic primer. Aluminum Siding: Remove all chalk or loose paint. Clean surface thoroughly with an aluminum siding cleaner. Apply two coats of this product.

## APPLICATION

Stir paint thoroughly. Apply generously with a nylon or polyester brush. For large areas use a medium nap roller. Do not paint in direct sunlight. On hot days surface may be dampened with water prior to painting to keep paint from drying too quickly. Stop painting at least four hours before nightfall. This product may be applied when air and surface temperatures are as low as 45° F and are expected to remain as such for a period of 48 hours after application. Do not paint if rain is expected within 24 hours. Apply two coats for a longer lasting paint job. If using two or more gallons of the same color, mix together and stir paint thoroughly to make sure color is uniform though out.

## WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Yenkin-Majestic Paint Corp. 1920 Leonard Ave. Columbus, OH 43219 Ph: (800) 848-1898 Fx: (614) 258-3062

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

REVISED DATE 4/3/2014