

## **MAJIC® BARRICADE®**

### Latex Drywall Primer/Sealer

#### FEATURES

- Seals new drywall & plaster
- High Hiding
- Quick Drying
- Superior holdout
- Improved appearance of topcoat

#### DESCRIPTION & USES

A quick drying, water base primer for interior drywall, acoustical tile, and masonry. It seals wallboard and joint compound, providing excellent hold-out for application of the finish coat. This primer is an ideal base for latex and alkyd enamels, as well as epoxy coatings. It will provide a smooth finish and even sheen to the topcoat appearance.

#### PRODUCTS & SIZES

Available in white. 1-gallons and 5-gallon sizes standard.

#### SURFACE PREPARATION

Surface to be primed must be clean, dry & free of dirt, wax, oil, sanding dust, paste and water-soluble residue. To wash surface, use a water-based, phosphate-free, detergent and rinse well with clean water. Remove mildew using 1 quart bleach to 3 quarts water, scrub surface and then rinse with clean water. Wear goggles and gloves to prevent contact with bleach. Loose paint should be removed by scraping and sanding. Repair holes and cracks with spackling compound - sand smooth. Dull glossy areas with sandpaper, or appropriate sanding agent. If using a liquid sander, or de-glosser, follow directions carefully, and test a small area for compatibility with this primer. Bleeding stains (smoke, ink, water, crayon, etc.) must be sealed with appropriate stain-blocking primer

#### APPLICATION

Do not apply at temperatures below 50° F (air & surface temps). Stir paint thoroughly. Apply generously with a high-quality nylon, or polyester, brush and/or medium nap roller cover. For airless spray, use an .018 reversible tip @ 1500-2000 psi. **DO NOT THIN.** To minimize "joint banding" with sheened finishes, apply a first coat of primer over the tape joints, followed by one full primer coat over the entire job.

Method of Application: Brush, roller or spray.

Drying: Normal drying is 30 minutes to touch at 77F (25C) and 50% humidity. Temperature and humidity may affect drying time.

Clean Up: Soap and water immediately after use.

#### PHYSICAL PROPERTIES

<b>RESIN TYPE</b>	Vinyl acrylic
<b>SOLVENT</b>	Water
<b>GLOSS</b>	<5 @ 60°
<b>VOC</b>	<50 grams/liter
<b>FILM THICKNESS</b>	4.5 Mils <b>Wet</b> 1.25 Mils <b>Dry</b>
<b>COVERAGE</b>	350 sq. ft./gallon
<b>DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY</b>	30 Minutes <b>To Touch</b> 2 Hours <b>To Recoat</b> 7-14 Days <b>Full Cure</b>
<b>WEIGHT SOLIDS</b>	47% ± 2%
<b>VOLUME SOLIDS</b>	29% ± 2%
<b>FLASH POINT</b>	N/A

**Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • [www.majicpaints.com](http://www.majicpaints.com)**

#### Caution:

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.