

MAJIC[®] TIRE PAINT**FEATURES**

- Dries to smooth black satin finish
- Quick drying
- Moisture resistant
- No color rub-off (even when wet)
- Protects tires from elements

DESCRIPTION & USES

Majic Tire Paint is a water-based acrylic designed for application to used and retread tires.

PRODUCTS & SIZES

8-0018 Black. Available in pints.

SURFACE PREPARATION

Surface must be clean, dry and free of oils, grease and loose dust, dirt or other surface contaminants. Stubborn dirt may be removed by scrubbing with a mild detergent solution, rinse with clean water, and allow to dry. Remove grease, oils and wax by wiping surface with Mineral Spirits and allow to dry.

APPLICATION

Shake product thoroughly before use. Majic Black Tire Paint may be applied by brush, cloth or pad. May also be applied, full strength, by low pressure spray. DO NOT THIN. Apply by brush, cloth or pad in thin coats. 2 coats, applied at 1.5 – 2.0 mils each, will yield 1.0 mils of Dry Film Thickness. Do not apply within 4 hours of rainfall. Store this product at temps above 50° F and below 100° F. Do not freeze. For spills, soak up with absorbent material or rags and dispose of in accordance with local, state, and federal regulations.

Method of Application: Brush, roller or spray.

Drying: To touch: 20 minutes. To handle: 1 hour. To recoat: 4 hours. Dry time may be affected by temperature and humidity

Clean Up: Clean up tools, equipment, and spills with warm, soapy water.

PHYSICAL PROPERTIES

RESIN TYPE	Acrylic
SOLVENT	Water
VOC	46 grams/liter
FILM THICKNESS	4.0 Mils Wet 1.0 Mils Dry
COVERAGE	400 sq. ft./gal @ 1.0 mil DFT
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	1 Hour To Handle 4 Hours To Recoat 7-14 Days Full Cure
VOLUME SOLIDS	21% ± 2%

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.