

MAJIC® BARRICADE®

Odor Eliminator Oil-Based Primer

FEATURES

- Primes & Seals interior wood, drywall, plaster, and concrete surfaces
- Excellent stain & odor blocking properties
- Quick drying- recoat in 2 hours
- May be top coated with Latex or Oil paints
- VOC compliant

DESCRIPTION & USES

Barricade Odor Eliminator is a specialty fast-dry alkyd primer, for application beneath carpet & floor coverings, to lock-in odors, and block bleeding stains. As an odor eliminator beneath carpet, vinyl & tile floors For blocking water & smoke stains. Interior use only - Do not apply to surfaces below 50 degrees F Not recommended as a floor primer beneath liquid coating

PRODUCTS & SIZES

White (Tintable up to 2 ounces universal colorant per/gal)
Available in 1 gallon & 5 gallon containers

SURFACE PREPARATION

Barricade Odor Eliminator Primer is effective at blocking many “bleeding” stains including water, tannin, graffiti, rust/smoke, and seals/eliminates most pet stain odors. Barricade Odor Eliminator Primer may be applied direct to interior wood, cured plaster, drywall, or to previously painted surfaces. Barricade Odor Eliminating Primer may be used on clean, dry concrete surfaces that have aged at least 90 days – For best adhesion to concrete floors, sand or abrade surface to create a “profile” for a strong mechanical bond with primer. This product will adhere to most clean metals, but is not recommended for use on new, or unpainted galvanized metal. All surfaces to be primed/sealed must be clean, dry, and free of dirt, dust, grease/wax/oil, peeling or loose paint, rust, chalk, mold/milder or other surface contaminants that may interfere with penetration and adhesion of the primer – when priming over stained surfaces, remove as much of the stain as possible by washing, sanding, scraping, etc. Glossy, slick surfaces should be sanded with a medium grit paper to ensure proper adhesion.

APPLICATION

Majic Barricade Odor Eliminating Primer is ready to apply by brush, roller, or spray application – No reduction is required, not recommended. For best results, apply between 2.6 – 4.0 mils wet (yields 1.5 – 2.3 mils dry). Allow to dry a minimum of 2 hours before re-coating, or top coating. Majic Barricade Odor Eliminating Primer may be finished with Latex, or Oil based finishes. In most cases, stains/odors will be sealed in a one-coat application. Heavy, or difficult stains/odors may be best sealed by spray application – if a second coat is necessary for such, allow 16-24 hours between coats of Majic Barricade Odor Eliminating Primer.

Method of Application: Brush, roller, or spray.

Drying: Normal drying is 30 minutes to touch at 77F (25C) and 50% humidity, 2 hours to recoat or sanding. Temperature and humidity may affect drying time.

Clean Up: Clean all tools, equipment and spills with Mineral Spirits or VM&P Naptha

PHYSICAL PROPERTIES

RESIN TYPE	Alkyd
SOLVENT	VT Alkyd/Oil
GLOSS	0-5 @ 60°
VOC	<350 grams/liter
FILM THICKNESS	4 Mils Wet
	1.25 Mils Dry
COVERAGE	400-450 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	1 Hour To Touch
	2 Hours To Recoat
	7-10 Days Full Cure
WEIGHT SOLIDS	79% ± 2%
VOLUME SOLIDS	58% ± 2%
FLASH POINT	68°F

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.