

MAJIC® OIL BASE FLOOR PAINT

FEATURES

- Applies easily
- For concrete, wood, and properly primed metal
- Scuff, mar, and water resistant
- VOC compliant in most states

DESCRIPTION & USES

A durable oil base enamel that will give dependable, long-lasting protection in all climates. Majic Oil Base Floor Paint is specifically formulated for ease of application and trouble-free performance.

PRODUCTS & SIZES

Gallons and quart sizes standard. 8 ready-mix colors and tinting bases.

SURFACE PREPARATION

New Wood: Apply 2 coats, allowing a minimum 24 hours dry time between coats. **Painted Wood:** Remove loose and peeling paint. Thoroughly wash surface with a cleaner and rinse to removed dirt, wax and other contaminants. Prime bare areas with Majic Oil Base Floor Paint. When dry, lightly sand and follow with 1-2 coats of Majic Oil Base Floor Paint. **New Concrete:** Majic Oil Base Floor Paint should not be applied to concrete which is positioned on ground without a moisture barrier. Allow new concrete to cure 90 days. Prior to painting, etch surface with a 10% solution of muriatic acid. Wear gloves and goggles to prevent contact with the acid. Rinse thoroughly and allow to dry completely. Follow with 2 coats of Majic Oil Base Floor Paint. Do not paint if floor is cold or room is cold and damp. **Painted Concrete:** Remove loose and peeling paint. Thoroughly wash surface with a cleaner and rinse to removed dirt, wax and other contaminants. Prime bare areas with Majic Oil Base Floor Paint. **Galvanized Metal:** Check for stabilizing film, remove appropriately and prime with either 8-0070 Majic Self-Etching Primer or a 8-0009 Majic Universal Acrylic Primer. Follow with 1-2 coats of Majic Oil Base Floor Paint.

APPLICATION

Stir thoroughly until paint is uniform. If using 2 or more containers of the same color, mix together and stir paint thoroughly to ensure color is uniform throughout. Apply smoothly and evenly with a high-quality nylon brush, short nap roller, roller or pad applicator. Do not paint exterior if surface temperature is below 50°F (10°C), in direct sun light, or if rain is expected within 24 hours. Let dry overnight before opening to traffic.

Drying: Normal drying is 8 hours to touch and 24 hours to recoat, at 77F (25C) and 50% humidity. Temperature and humidity will affect drying time. Allow 24 hours between coats. **Note:** Painted surfaces may become slippery when wet. **DO NOT OVER-APPLY.** Proper drying and curing time may significantly slow if applied in excess of 3.0 mils wet, or if recoating too soon.

Clean Up: Mineral spirits immediately after use.

PHYSICAL PROPERTIES

RESIN TYPE	Alkyd
SOLVENT	Mineral Spirits
GLOSS	80% + @ 60°
VOC	<340 grams/liter
FILM THICKNESS	2.5 Mils Wet 1.4 Mils Dry
COVERAGE	600-700 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	5 - 10 Hours To Touch 24 Hours To Recoat 7-14 Days Full Cure
WEIGHT SOLIDS	70% ± 2%
VOLUME SOLIDS	57% ± 2%
FLASH POINT	>105°F

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.