

## MAJIC® LATEX FLOOR PAINT

### FEATURES

- Applies easily
- For concrete, wood, and properly primed metal
- Scuff, mar, and water resistant

### DESCRIPTION & USES

Majic Interior/Exterior Latex Floor Paint is a latex enamel for all walked-on surfaces that provides beautiful, trouble free protection against weather.

### PRODUCTS & SIZES

8-0120 Battleship Gray, 8-0121 Tile Red, 8-0122 Dark Brown, 8-0123 Colonial Green, 8-0124 Light Gray. Available in gallons and quarts.

### SURFACE PREPARATION

**New Wood:** Be sure the surface is sanded smooth and free of dirt and dust. **Previously Painted Wood:** Remove any loose paint, dirt, grease, or wax from the surface. Spot prime bare wood areas with Majic Latex Floor Paint. Sand any glossy areas. **New Concrete:** Allow the freshly poured concrete to age at least 90 days before painting. For best results, smoothly troweled surfaces should be etched with a solution of 1 part muriatic acid to 3 parts water then rinsed thoroughly. Wear goggles and gloves to prevent contact with the acid. **Previously Painted Concrete:** Remove all loose paint, dirt, grease or wax. Cleaning is best accomplished using a strong solution of trisodium phosphate. Wear goggles and gloves to prevent contact with the trisodium phosphate. Rinse thoroughly, sweeping water with a broom. Spot prime bare areas with Majic Latex Floor Paint.

### APPLICATION

Do not paint at surface temperatures below 50 0 F. Stir the paint thoroughly until uniform. Apply generously using a good quality nylon brush or short nap roller. On unpainted wood two coats will be needed to seal the surface completely. Allow 8 hours drying between coats. Paint may be applied to slightly damp surfaces but should not be applied during or within 12 hours of expected rain. Painted surfaces may be walked on after drying overnight. Textured surfaces or extreme color changes may require a second application. When using two or more gallons of the same color, mix paint together to assure uniform color. **DO NOT THIN.**

### PHYSICAL PROPERTIES

<b>RESIN TYPE</b>	Acrylic Polymer Emulsion
<b>SOLVENT</b>	Water
<b>GLOSS</b>	10-20 @ 60°
<b>VOC</b>	<100 grams/liter
<b>FILM THICKNESS</b>	3.0 Mills <b>Wet</b>
	1.0 Mills <b>Dry</b>
<b>COVERAGE</b>	Up to 400 sq ft/gal
<b>DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY</b>	2 Hours <b>To Touch</b>
	8 Hours <b>To Recoat</b>
	7-14 Days <b>Full Cure</b>
<b>VISCOSITY</b>	74-78 KU
<b>FINISH</b>	Semi-Gloss
<b>FLASH POINT</b>	>200°F

**Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • [www.majicpaints.com](http://www.majicpaints.com)**

**Caution:**

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.