

MAJIC® PREMIUM ASPHALT FENCE PAINT**FEATURES**

- For use on exterior wood, masonry and concrete

DESCRIPTION & USES

Asphalt based fence paint fortified with special oils designed to penetrate, preserve and protect wood and other types of surfaces. It will also add years of service life as it rust proofs metal, preserves wood, damp proofs stone or brick and rejuvenates composition surfaces. Helps prevent cribbing on fencing and stalls. Designed for use above or below grade.

PRODUCTS & SIZES

8-0211-5 Black. Available in five gallons.

SURFACE PREPARATION

Surface must be thoroughly dry and clean, free of any dirt or contaminants.

APPLICATION

Surface shall be clean, dry and free of any dirt or contaminants. Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24- hour period. Do not apply if rain is imminent within 24 hours of application. Be sure to wear eye protection and gloves when mixing and applying this product. Stir container thoroughly. Apply by brush, roller or airless spray (suggested tip size .017 to .023). Although paint will cover in one coat, a second coat may be applied for optimum performance and durability. Clean tools with mineral spirits in well ventilated area immediately after use.

PHYSICAL PROPERTIES

RESIN TYPE	Asphalt/Oil
SOLVENT	Mineral Spirits
GLOSS	N/A
VOC	<250 grams/liter
FILM THICKNESS	5.0 Mills Wet 3.0 Mills Dry
COVERAGE	Up to 1,000 sq ft/5 gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	24 Hours To Touch 24 Hours To Recoat 7-14 Days Full Cure
VISCOSITY	65 - 70 KU
FINISH	Gloss
FLASH POINT	>200°F

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.