

MAJIC[®] POLYURETHANE WOOD COATING**FEATURES**

- Wear & weather resistant
- Hard protective finish
- Enriches the natural beauty of the wood
- Protects finish from abrasion, water, alcohol, cleaners and stains

DESCRIPTION & USES

A hard protective finish which offers long lasting beauty. This product provides a finish that is resistant to water, chemicals, detergents, alcohol, impact and abrasion. Formulated and recommended for application on bare wood to seal the wood and to provide a coating that can be sanded to create a smooth surface.

PRODUCTS & SIZES

8-0300 Clear Gloss, 8-0386 Clear Satin. Available in gallons, quarts and ½ pints.

SURFACE PREPARATION

New wood should be sanded thoroughly. Remove all traces of dust with a tack cloth. On previously finished wood, remove any shellac, lacquer or varnish with paint remover. All wax, grease or dust must be removed. Any finish in poor condition must be sanded smooth. Sand surface thoroughly and remove sanding dust with a tack cloth.

APPLICATION

Apply when surface and air temperature are 65° For higher. Stir gently, lifting from the bottom. DO NOT SHAKE. Apply with good quality brush, short nap roller or spray gun, using a minimum number of strokes. Recoat in 12 hours. Sand between coats for smoothest results. CAUTION: This product may be slippery when wet.

PHYSICAL PROPERTIES

RESIN TYPE	Alkyd
SOLVENT	Mineral Spirits
GLOSS	80+ @ 60°
VOC	<450 grams/liter
FILM THICKNESS	3.3 Mils Wet 1.3 Mils Dry
COVERAGE	Up to 600 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	4 Hours To Touch 12 Hours To Recoat 7-14 Days Full Cure
VISCOSITY	31-45" #4 FC
FINISH	Gloss Satin
FLASH POINT	>105°F

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.