

MAJIC® CAMOUFLAGE PAINT**FEATURES**

- Flat, non-reflective finish
- Perfect for use on vehicles, boats, trailers, duck blinds, free stands, ladders, ladder stands, guns, bows, etc.
- Provides camouflage with any nature background
- Water resistant

DESCRIPTION & USES

Majic camouflage paint offers a flat, non-reflective finish that is rust inhibiting and water resistant to protect wood and metal from the elements. The color selection is perfect for breaking up outlines and shapes with camouflage allowing you to blend with almost any nature background.

PRODUCTS & SIZES

8-0850 Olive Drab, 8-0851 Black, 8-0852 Khaki, 8-0853 Bark Gray, 8-0854 Earth Brown, 8-0855 Desert Tan. Available in gallons and quarts.

SURFACE PREPARATION

Bare Metal: Remove all rust scale with wire brush or sander. Remove oil or grease with paint thinner. Prime with rust inhibiting primer.
Painted Metal: Remove loose or peeling paint and rust scale with wire brush or sander. Remove oil or grease with paint thinner. Prime any bare metal with rust inhibiting primer.
Painted Surfaces: (General) Make sure surface is clean, dry and free of loose paint, dirt, wax, grease, etc. Sand glossy areas. Spot prime absorbent areas.

APPLICATION

Stir thoroughly. Apply with a high quality brush, roller, paint pad or by spray equipment. Where necessary, apply a second coat and allow each coat to dry thoroughly before applying the next coat. Do not apply if surface temperature is below 50° F (10° C) or in direct sunlight. On unpainted surfaces, sand lightly and apply two coats for best results, sanding lightly between coats.

PHYSICAL PROPERTIES

RESIN TYPE	Alkyd
SOLVENT	Aliphatic
GLOSS	0-3 @ 60°
VOC	<340 grams/liter
FILM THICKNESS	3.0 Mils Wet
	1.5 Mils Dry
COVERAGE	Approx 450 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	5-10 Hours To Touch
	24 Hours To Recoat
	7-10 Days Full Cure
VISCOSITY	90-95 KU
FLASH POINT	108°F
FINISH	Flat

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.