

MAJIC® EASY SLIP**Dry Film Lubricant Graphite Based Coating****FEATURES**

- Bonds quickly to clean metal, wood, concrete and most plastic surfaces
- Perfect for use on farm and industrial equipment, gravity boxes, corn picker heads, combines, truck & wagon beds, buckets, blades, garage door tracks, snow blowers, lawn & garden tools, saw blades, dump bins, solar panel coating, snow plow blades and lawn mower decks

DESCRIPTION & USES

Majic Easy Slip is a black graphite coating that bonds quickly to any clean metal, wood, concrete and most plastic surfaces and provides a smooth, low-friction coating.

PRODUCTS & SIZES

8-0870 Black. Available in gallons.

SURFACE PREPARATION

Bare Metal: Remove all rust scale with wire brush or sander. Remove oil or grease with paint thinner. **Painted Metal:** Remove loose or peeling paint and rust scale with wire brush or sander. Remove oil or grease with paint thinner. **Painted Surfaces: (General)** Make sure surface is clean, dry and free of loose paint, dirt, wax, grease, etc. Sand glossy areas.

APPLICATION

Stir thoroughly. Apply with a high quality brush, roller, paint pad or by spray equipment. Where necessary apply a second coat and allow each coat to dry thoroughly before applying the next coat. Do not apply if surface temperature is below 50° F (10° C) or in direct sunlight.

PHYSICAL PROPERTIES

RESIN TYPE	Acrylic Copolymer
SOLVENT	Aromatic Alcohol
GLOSS	0-5 @ 60°
VOC	N/A
FILM THICKNESS	2.0 – 3.0 Mils Wet 0.8 – 1.2 Mils Dry
COVERAGE	Approx 450 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	2 Hours To Touch 8 Hours To Recoat 7-10 Days Full Cure
VISCOSITY	50 - 70 sec #2 Zahn
FLASH POINT	< 50°F
FINISH	Matte

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.