

## MAJIC® TOWN & COUNTRY® Tractor, Truck & Implement Enamel

### FEATURES

- Outstanding Durability
- Excellent Adhesion
- Corrosive Resistant
- High Gloss Finish
- VOC Compliant / Environmentally Friendly
- Can be used with Majic Catalyst / Hardener

### DESCRIPTION & USES

Majic Town & Country Tractor, Truck & Implement Enamel is a durable heavy-duty alkyd enamel specially formulated for excellent adhesion, and resistance to weathering and corrosion. It may be applied by brush or spray, and dries to a high gloss finish. For use on iron, steel, aluminum and properly primed galvanized metal.

### PRODUCTS & SIZES

8-0951 IH White, 0952 NH Yel, 0953 Rustic Brwn, 0954 Ford Red, 0955 MF Gray, 0956 NH Red, 0957 New JD Yel, 0958 Case Orange, 0959 Matte Blk, 0961 MF Red, 0962 Cat Yel, 0964 JD Yel, 0965 AC Orange, 0966 JD Green, 0967 Lt Ford Gray, 0968 Ford Blue, 0971 Kubota Orange, 0972 IH Red, 0973 Schl Bus Yel, 0974 Oliver Green, 0979 New Ford/NH Blue, 0983 Case Power Yellow, 0984 Alum, 0990 White, 0994 Blk. Available in gallons and quarts.

### SURFACE PREPARATION

Surface to be coated must be dry, clean, sound and free from all contamination including loose and peeling paint, dirt, grease, oils, wax, and other surface contaminants that may inhibit the product's tight adhesion to the substrate. Remove oils, grease and wax with paint thinner, Remove poorly adhering paint by sanding or wire brush. Prime any bare metals with appropriate primer. Rusted metal should be sanded, wire-brushed, or ground to clean shiny metal before painting. In Repaint Applications – Existing paint must be clean, dry and tightly adhering to surface. Spot prime bare metal with appropriate primer. Sand all glossy surfaces prior to painting. Ferrous Metal: Surface must be thoroughly cleaned to remove any dust, rust and surface contaminants. Prime with Majic 8-0986 Gray, or 8-0989 Red Oxide Rust Inhibiting Primer. Aluminum: Bare aluminum may be primed with Majic 8-0986 Gray, or 8-0989 Red Oxide Rust Inhibiting Primer, following necessary and proper surface preparation that may include a metal pre-treatment wash and surface sanding. Galvanized Metal: After necessary and thorough cleaning & preparation, prime with Majic Truck & Auto Industrial Acrylic Primer 8-4986, or any non-cementitious primer designated for galvanized surfaces.

### APPLICATION

Product may be applied by brush, roller or spray. Equipment, pressure and/or tip size may need to be adjusted, or changed, depending on conditions, temperatures and humidity at time of application. Stir paint thoroughly. Apply by high quality brush, roll or spray at a rate not greater than 2.5 mils Wet Film Thickness. When spraying, add 1 pint of Majic Reducer 8-0750 per gallon of enamel. For best results, apply 2 coats of Majic Town & Country Tractor, Truck & Implement Enamel, sanding lightly between coats. Allow 24 hours to dry between coats. For greater hardness and corrosion resistance, higher gloss and a faster cure time, add ½ pint of Majic Catalyst/ Hardener 8-0950 per 1 gallon of Majic Town & Country Tractor, Truck & Implement Enamel, in strict accordance to package directions. NOTE: Proper drying and cure requires strict adherence to recommended applied film thickness. Heavier application than recommended, or recoating too soon will result in a significantly slower dry time, and overall cure. Do not apply in direct sunlight or when surface temperatures are below 50°F. Apply only when surface temperature is 5°F above the dew point. Avoid application late in the day when dew and condensation are likely to form, or if rain is expected. All oil/alkyd products change color with age.

### PHYSICAL PROPERTIES

<b>RESIN TYPE</b>	Soya/Alkyd Resin
<b>SOLVENT</b>	Mineral Spirits, Naptha
<b>GLOSS</b>	Gloss: 80+ @ 60° Matte: 10 @ 60°
<b>VOC</b>	340 gms/ltr
<b>FILM THICKNESS</b>	2.5 Mils <b>Wet</b> 1.3 Mils <b>Dry</b>
<b>COVERAGE</b>	600-700 sq. ft./gal
<b>DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY</b>	5-10 Hours <b>To Touch</b> 24 Hours <b>To Recoat</b> 7-14 Days <b>Full Cure</b>
<b>VISCOSITY</b>	83-88 KU
<b>FLASH POINT</b>	> 105° F
<b>FINISH</b>	Gloss/Matte

**Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • [www.majicpaints.com](http://www.majicpaints.com)**

**Caution:**

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.