

MAJIC® EASY SPREAD Interior Latex Drywall Primer

FEATURES

- Dries quickly
- Promotes adhesion
- For use under oil or latex paint
- Easy to apply

DESCRIPTION & USES

This is a latex base primer that seals unpainted surfaces providing a base for latex or oil base finish coats. It dries quickly and is ready for recoating in just a few hours. It will not raise the nap on wallboard and prevents flashing or hot spots from appearing in the finish coat. It applies easily with brush, roller or spray. USE IT ON: Drywall, masonry, and wood.

PRODUCTS & SIZES

8-1090 White. Available in 1 gallon, 2 gallon & 5 gallon containers.

SURFACE PREPARATION

The surface to be painted must be clean and free of dirt wax, oil, grease, paste and water soluble residue. If washing the surface is necessary, use a water based, low sudsing detergent and rinse well with clean water. Let dry thoroughly. Remove any mildew using one quart of household bleach in three quarts of water. Rinse thoroughly and let dry. Wear goggles and gloves to prevent contact with the bleach. Loose and scaling paint should be removed by scraping or sanding. Repair holes, crevices and cracks with spackling compound, and sand smooth. Dull glossy areas with sandpaper or surface prep agent. Stains from water, smoke, ink and crayon should be covered with an alcohol base or alkyd stain blocking primer.

APPLICATION

Do not paint at temperatures below 50° F. Stir the paint thoroughly. Apply generously with a good quality nylon or polyester brush or medium nap roller. First paint a 2 to 3 inch strip at the ceiling and baseboard, around windows and doors, and in corners with a sash brush. Overlap these brushed areas as much as possible as you continue painting with the roller. Do not spread paint too far. One roller-full should cover an area approximately 3' x 3'. Use a 3/8" to 1/2" nap roller for large areas. To minimize "joint banding" in semi-gloss and gloss finishes, apply a first coat of primer over the tape joints followed by one full primer coat over the entire job. DO NOT THIN.

PHYSICAL PROPERTIES

RESIN TYPE	Vinyl Acrylic Latex
SOLVENT	Water
GLOSS	2-5 @ 60°
VOC	<100 grams/liter
FILM THICKNESS	4.5 Mils Wet 1.0 Mils Dry
COVERAGE	Up to 300 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	1 Hour To Touch 2-4 Hours To Recoat 7-10 Days Full Cure
VISCOSITY	95-105 KU
FLASH POINT	> 200°F
FINISH	Flat

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.