

MAJIC® EASY SPREAD

Interior Latex Eggshell Wall Paint

FEATURES

- For ceilings, walls and trim
- Tools rinse clean in soapy water
- Dries in minutes
- Applies easily

DESCRIPTION & USES

Easy Spread Interior Latex Eggshell Wall Paint is designed to provide a decorative stain resistant finish for interior walls and ceilings.

PRODUCTS & SIZES

8-1200 White, 8-1220 White Tint Base #1. Available in gallons.

SURFACE PREPARATION

The surface to be painted must be clean and free of wax, oil, grease, paste and water soluble residue. If washing the surface is necessary, use a water based, low sudsing detergent and rinse well with clean water. Remove any mildew using one quart of household bleach in three quarts of water. Rinse thoroughly. Wear goggles and gloves to prevent contact with the bleach. Loose and scaling paint should be removed by scraping or sanding. Repair holes, crevices and cracks with spackling compound, sand smooth, and prime. Dull glossy areas with sandpaper or surface prep agent. If using a liquid deglosser or primer, follow the directions closely and test a small area for compatibility with the finish coat. Stains from water, smoke, ink and crayon will bleed through most paint. Cover these areas with an alcohol base or alkyd stain blocking primer. **NEW SURFACES: DRYWALL AND MASONRY:** Prime with one coat of interior latex primer. Finish with two coats of Easy Spread Interior Latex Eggshell Wall. **INTERIOR WOOD:** Apply one primer coat, using an alkyd enamel undercoat. Apply two finish coats of Easy Spread Interior Latex Eggshell Wall. **FERROUS METALS:** Prime with one coat of an alkyd enamel undercoat or rust inhibiting primer. Finish with two coats of Easy Spread Interior Latex Eggshell Wall. **ALUMINUM:** Apply one coat acrylic latex metal primer. Finish with two coats of Easy Spread Interior Latex Eggshell Wall. **GALVANIZED METAL:** Check for stabilizing film, remove appropriately and prime with latex galvanized primer. Finish with two coats of Easy Spread Interior Latex Eggshell Wall.

APPLICATION

Do not paint at temperatures below 50° F. Stir the paint thoroughly. Apply with a good quality nylon/polyester brush or short to medium nap roller. First paint a 2 to 3 inch strip at the ceiling and baseboard, around windows and doors, and in corners with a sash brush. Overlap these brushed areas as much as possible as you continue painting with the roller. Do not spread paint too far. One roller-full should cover an areas approximately 3' x 3'. Do not subject the finish to washing for at least 30 days. This paint will cover most surfaces in one coat. Textured surfaces or extreme color changes may require a second application. When using two or more gallons of the same color, mix paint together to assure uniform color. **DO NOT THIN.**

PHYSICAL PROPERTIES

RESIN TYPE	Vinyl Acrylic Latex
SOLVENT	Water
GLOSS	5-15 @ 60°
VOC	<50 grams/liter
FILM THICKNESS	3.2 Mils Wet
	0.8 Mils Dry
COVERAGE	Up to 300 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	1 Hour To Touch
	8 Hours To Recoat
	7-10 Days Full Cure
VISCOSITY	92-96 KU
FLASH POINT	> 200°F
FINISH	Eggshell

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.