

## MAJIC® EASY SPREAD

### Interior Latex Semi-Gloss Wall Paint

#### FEATURES

- For woodwork, walls and trim
- Dries in minutes
- Tools rinse clean in soapy water
- Applies easily

#### DESCRIPTION & USES

This is an economical quality vinyl-acrylic formulation that offers dependable performance and exceptional value as modern latex enamel for primed or previously painted drywall, plaster, wood or metal. Dirt and grease are easily removed from the finish by simply wiping with a rag and soapy water. Majic Easy Spread Interior Latex Semi-Gloss Enamel dries to a tough semi-gloss finish coat.

#### PRODUCTS & SIZES

8-1300 White, 8-1310 Off White, 8-1311 Antique White, 8-1312 Bone White, 8-1319 Satinwood, 8-1320 White TB #1, 8-1337 Mist Gray, 8-1369 Sea Foam, 8-1371 Lagoon Blue. Available in gallon, 2 gallon and 5 gallon containers.

#### SURFACE PREPARATION

The surface to be painted must be clean and free of dirt, wax, oil, grease, paste, corrosion and water soluble residue. If washing the surface is necessary, use a water based, low sudsing detergent and rinse well with clean water. Remove any mildew using one quart of household bleach in three quarts of water. Rinse thoroughly. Wear goggles and gloves to prevent contact with the bleach. Loose and scaling paint should be removed by scraping or sanding. Repair holes, crevices and cracks with spackling compound, and sand smooth. Spot prime these areas. Dull glossy areas with sandpaper or surface prep agent. If using a liquid deglosser or primer, follow the directions closely and test a small area for compatibility with the finish coat. Stains from water smoke, ink and crayon will bleed through most paint. Cover these areas with an alcohol base or alkyd stain blocking primer. See label directions for priming requirements for specific surfaces. **NEW SURFACES: DRYWALL AND MASONRY:** Prime with one coat of interior latex primer. Finish with two coats of Easy Spread Interior Latex Semi-Gloss Wall. **INTERIOR WOOD:** Apply one primer coat, using an alkyd enamel undercoat. Apply two finish coats of Easy Spread Interior Latex Semi-Gloss Wall. **FERROUS METALS:** Prime with one coat of an alkyd enamel undercoat or rust inhibiting primer. Finish with two coats of Easy Spread Interior Latex Semi-Gloss Wall. **ALUMINUM:** Apply one coat acrylic latex metal primer. Finish with two coats of Easy Spread Interior Latex Semi-Gloss Wall. **GALVANIZED METAL:** Check for stabilizing film, remove appropriately and prime with latex galvanized primer. Finish with two coats of Easy Spread Interior Latex Semi-Gloss Wall.

#### APPLICATION

Do not paint at surface temperatures below 50° F. Stir the paint thoroughly. Apply generously with a good quality nylon or polyester brush or medium nap roller. First paint a 2 to 3 inch strip at the ceiling and baseboard, around windows and doors, and in corners with a sash brush. Overlap these brushed areas as much as possible as you continue painting with the roller. Do not spread paint too far. One roller-full should cover an area approximately 3' x 3'. Do not subject the finish to washing for at least 30 days. This paint will cover most surfaces in one coat. Textured surfaces or extreme color changes may require a second application. When using two or more gallons of the same color, mix paint together to assure uniform color. **DO NOT THIN.**

#### PHYSICAL PROPERTIES

<b>RESIN TYPE</b>	Vinyl Acrylic Latex
<b>SOLVENT</b>	Water
<b>GLOSS</b>	15-40 @ 60°
<b>VOC</b>	<50 grams/liter
<b>FILM THICKNESS</b>	4.7 Mils <b>Wet</b> 1.0 Mils <b>Dry</b>
<b>COVERAGE</b>	Up to 300 sq ft/gal
<b>DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY</b>	1 Hour <b>To Touch</b> 8 Hours <b>To Recoat</b> 7-10 Days <b>Full Cure</b>
<b>VISCOSITY</b>	92-96 KU
<b>FLASH POINT</b>	> 200°F
<b>FINISH</b>	Semi-Gloss

**Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • [www.majicpaints.com](http://www.majicpaints.com)**

**Caution:**

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.