

MAJIC® NWP NATURAL WOOD PROTECTANT®

Semi-Transparent Latex House & Deck Stain

FEATURES

- Superior protection for exterior wood
- Provides excellent water repellency
- Perfect for deck floor boards, rails, spindles, fences, decorative trim, wood lawn furniture, and exterior wood siding

DESCRIPTION & USES

Majic Semi-Transparent Wood Stain provides a mildew resistant, water repellent coating for pressure treated and untreated wood decks, siding, and fences. Beautiful colors protect wood against moisture, swelling, cracking, warping, splintering and discoloration. For Exterior Wood Surfaces, only.

PRODUCTS & SIZES

8-1420 Cedar, 8-1424 Redwood, 8-1426 Russet Brown, 8-1428 Cape Cod Gray. Available in gallons.

SURFACE PREPARATION

The surface must be clean and free of all dirt, mildew, loose wood fibers, and other foreign matter. Dirt, dust, etc. may be cleaned with commercially available Deck Cleaners or Brighteners (in strict accordance to mfr's directions), or by scrubbing surface with a mild, phosphate free detergent & water solution. 1 cup of household bleach may be added to 1 gallon detergent solution to remove mildew stains. Rinse thoroughly with clean water to neutralize, prior to staining. Necessary for Majic Semi-Transparent Stain to be effective, and to provide the type of protection described above, the stain must be able to penetrate the wood surface. Surface must be sound, clean and completely dry (moisture content must be below 15%, or wood must be exposed to dry, warm weather for a minimum of 5 days). Check for dryness by sprinkling water on wood to be stained. If the water is absorbed rapidly into surface, wood is ready for Majic Semi-Transparent Wood Stain application. If water is not rapidly absorbed into surface, allow the wood to weather until water is quickly absorbed into the surface. Prior to stain application, deck boards should be sanded (1) on new wood to remove mill glaze and to create better absorption of material, (2) on weathered wood to remove splinters and loose, dead (gray) fiber from board's surface, or (3) on previously sealed board, to remove any remnant of sealer, for greater absorption into surface. Majic Semi-Transparent Stain is not recommended for use over existing paints or solid color stains, as they will block penetration into the surface. Existing Paints or Solid color stains should be removed chemically, or by sanding with a coarse grit paper.

APPLICATION

Majic Semi-Transparent Stain should be shaken, or stirred, thoroughly before, and during, use. DO NOT DILUTE WITH ADDITIONAL WATER. Apply with a nylon, or polyester brush, roller or by spray. Do NOT over-apply. When spraying or rolling, always back brush immediately to assure uniform coverage and appearance. To minimize lap marks, stain three to four boards, always working from the wet edge of the job. The color of this product may vary dependent on species of wood, age, graying, grain pattern, heartwood content, number of applied coats, and thoroughness of mixing. Allow to dry in precipitation free weather for 24 hours. Once coat of Majic Semi-Transparent Stain, applied to a properly prepared surface, is generally sufficient. If a second coat is desired, allow to dry for 24 - 48 hours. NOTE TO USER: The appearance of a semi-transparent stain will vary depending on the porosity of the wood surface. To ensure desired appearance and proper dry time, always finish a small test area before proceeding. CLEAN TOOLS IN WARM, SOAPY WATER. KEEP FROM FREEZING

PHYSICAL PROPERTIES

RESIN TYPE	Acrylic Latex
SOLVENT	Water
GLOSS	<10 @ 60°
VOC	<150 grams/liter
FILM THICKNESS	3.0 Mils Wet 0.5 Mils Dry
COVERAGE	Up to 300 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	2-4 Hours To Touch 24 Hours To Recoat 7-10 Days Full Cure
VISCOSITY	70-75 KU
FLASH POINT	> 200°F
FINISH	Matte

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.