

MAJIC® LIFESTYLE®

Satin and Flat Paint & Primer

FEATURES

- Advanced formula designed to consolidate all of your painting needs into one product
- Interior / Exterior Paint & Primer
- Excellent Coverage
- Easy Stain Removal
- Fast & Easy Cleanup
- Mildew Resistant Coating

DESCRIPTION & USES

This is a high hiding, satin or flat finish that features good film build for an even roller texture over drywall and tape joints. One coat will hide most surfaces in good repaint condition. Interior & Exterior Latex Paint & Primer is recommended wherever a good quality, high-hiding satin or flat finish is required. USE IT ON: Self-priming on clean and properly prepared drywall, masonry, and plaster. May also be used on wood or primed metal.

PRODUCTS & SIZES

Available in gallons. Satin: 8-1870 White Snowfall, 8-1871 Tulip, 8-1872 Twine, 8-1873 Shore, 8-1874 Pebble, 8-1875 Peak, 8-1876 Meadow, 8-1877 Ripple, 8-1867 White TB, 8-1868 Mid-Tone TB, 8-1869 Clear TB. Flat: 8-1880 White Snowfall.

SURFACE PREPARATION

The surface to be painted must be clean and free of dirt, wax, oil, grease, paste and water soluble residue. If washing the surface is necessary, use a water based, low sudsing detergent and rinse well with clean water. Remove any mildew using one quart of household bleach in three quarts of water. Rinse thoroughly. Wear goggles and gloves to prevent contact with the bleach. Loose and scaling paint should be removed by scraping or sanding. Repair holes, crevices and cracks with spackling compound, and sand smooth. Dull glossy areas with sandpaper or surface prep agent. If using a liquid de-glosser or primer, follow the label directions closely and test a small area for compatibility with the finish coat. Stains from water, smoke, ink and crayon will bleed through most paint. Cover these areas with a pigmented shellac (interior only), or alkyd stain blocking primer. Satisfactory results can be obtained on most wood, and wallboard surfaces with two coats of this product. Some types of wallboard and joint compound, however, require a good latex primer sealer for best appearance. Many exterior woods contain water-soluble acids, or extractive stains, that may require an oil/alkyd stain-blocking primer to minimize, or eliminate, stain bleed-through. Be sure to follow label instructions regarding proper application & recoat times.

APPLICATION

Do not paint at temperature below 50°F. Stir the paint thoroughly. Apply generously with a good quality nylon or polyester brush or medium nap roller. First paint a 2 to 3 inch strip at the ceiling and baseboard, around windows and doors, and in corners with a sash brush. Overlap these brushed areas as much as possible as you continue painting with the roller. Do not spread paint too far. One roller-full should cover an area approximately 3' x 3'. Use a 3/8" to 1/2" nap roller for large areas. For airless spray application, use a .017 to .018 reversible tip at 1,500 to 2,000 PSI. This paint may be thinned with up to 1/2 pint water per gallon for the first coat. Do not thin the finish coat or when doing one coat work. Do not subject the finish to washing for at least 30 days. Textured surfaces or extreme color changes may require a second application. When using two or more gallons of the same color, mix paint together to ensure uniform color.

PHYSICAL PROPERTIES

RESIN TYPE	Acrylic
SOLVENT	Water
GLOSS	Satin: 20 - 35 @60 ° Flat: 0 - 5 @60 °
VOC	< 50 gm/ltr
RECOMMENDED FILM THICKNESS	4.0 – 5.0 Mils Wet 1.0 – 2.0 Mils Dry
COVERAGE	Up to 350 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	1 Hour To Touch 4 Hours To Recoat 7 Days Full Cure
FLASH POINT	>200°F
VISCOSITY	90 – 100
FINISH	Satin & F

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.