

MAJIC® EASY SPREAD

Exterior Latex Flat House Paint

FEATURES

- Applies easily
- Tools rinse clean in soapy water
- For wood and masonry
- Dries to a flat finish

DESCRIPTION & USES

A flat house paint formulated to provide a quality finish for your exterior house & trim.

PRODUCTS & SIZES

8-2000 White, 8-2029 Cape Cod Gray, 8-2031 Bark Brown, 8-2039 Stucco, 8-2041 Barn Red. Available in 1 gallon, 2 gallon & 5 gallon containers.

SURFACE PREPARATION

Previously Painted Wood: Scrape to remove loose, peeling paint and sand smooth. Remove all loose dirt and chalk. Scrub protected areas under eaves to remove invisible deposits which cause peeling. Remove any mildew using one quart of household bleach in three quarts of water. Rinse thoroughly. Wear goggles and gloves to prevent contact with the bleach. Sand any glossy areas to dull the surface. Caulk cracks and putty nail holes. Spot prime any bare areas with oil base exterior primer. **Previously Painted Masonry:** Remove loose or powdery paint and chalk. Spot prime bare areas with this product. **Metal Surfaces:** Scrape or wire brush to remove rust and loose paint. Spot prime bare metal with the proper metal primer. **New Unpainted Surfaces: Wood Siding & Trim:** Caulk cracks and joints, putty nail holes. Prime with an alkyd or acrylic latex exterior primer. **Masonry:** Newly poured concrete must be weathered a minimum of 90 days. Concrete block should be given two coats of Easy Spread Exterior Latex Flat House Paint. **Galvanized Metal** Check for stabilizing film, remove appropriately and prime with latex galvanized primer. **Ferrous Metal:** Prime with a red oxide rust inhibiting primer. **Bare Aluminum:** Prime with an acrylic latex primer.

APPLICATION

Stir thoroughly. Apply generously with nylon or polyester brush or good quality roller. Stop painting at least four hours before nightfall, stopping at the end of a wall or corner. Do not paint when temperatures are below 50° F, in direct sunlight, or before rain is expected within 24 hours. On hot days, surface may be dampened with water to slow drying. **DO NOT THIN.**

PHYSICAL PROPERTIES

RESIN TYPE	Vinyl Acrylic Latex
SOLVENT	Water
GLOSS	< 5 @ 60°
VOC	<100 grams/liter
FILM THICKNESS	5.0 Mils Wet 1.0 Mils Dry
COVERAGE	Up to 300 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	1 Hour To Touch 8 Hours To Recoat 7-10 Days Full Cure
VISCOSITY	92-98 KU
FLASH POINT	> 200°F
FINISH	Flat

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.