

**MAJIC® EASY SLIP**

## Non-Stick Lawn Mower Under Deck Spray

**FEATURES**

- Graphite coating prevents dirt, weeds, grass & snow from sticking to equipment and tools!
- Easy Slip is perfect for use on lawn mower decks, garage door tracks, snow blowers, garden tools, saw blades, etc.

**DESCRIPTION & USES**

Majic Easy Slip is a black graphite coating that bonds quickly to any clean metal, wood, concrete, and most plastic surfaces. For use on all types of equipment, truck and wagon beds, buckets, blades, garage door tracks, snow blowers, lawn and garden tools, saw blades, dump bins, solar panel coating, snow plow blades, and lawn mower decks.

**PRODUCTS & SIZES**

8-20024 Black. Available in 11 oz sprays.

**SURFACE PREPARATION**

Surface must be dry and free of dirt, dust, grease or wax. Protect surrounding area with drop cloths.

**APPLICATION**

Always apply paint at room temperature (70° - 80° F). To ensure color uniformity and prevent clogging, SHAKE CAN vigorously for at least one minute after mixing ball rattles. Hold can in an upright position 10" to 16" from the object being sprayed. Press spray button firmly. Use steady, even strokes while spraying. Several thin coats will result in a better finish than one heavy coat. If clogging develops remove spray button with a twisting motion and clean in mineral spirits. DO NOT STICK PIN OR OTHER OBJECT INTO CAN. Gently replace spray button with a twisting motion with the top of the can and spray button opening pointed away from you. Always clean spray button immediately after use by turning the can upside down and pressing the spray button until no more paint comes out.

**PHYSICAL PROPERTIES**

<b>RESIN TYPE</b>	Aromatic Alcohol Keytone
<b>SOLVENT</b>	Alkyd Copolymer
<b>VOC / MIR (sprays)</b>	2.10 grams/liter
<b>FILM THICKNESS</b>	<b>Mils Wet-</b> N/A
	<b>Mils Dry-</b> N/A
<b>COVERAGE</b>	Up to 20-30 sq ft/can @ 1 mil
<b>DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY</b>	1 Hour <b>To Touch</b>
	4-8 Hours <b>To Recoat</b>
<b>VISCOSITY</b>	N/A
<b>FLASH POINT</b>	< 50° F
<b>FINISH</b>	Matte
<b>GLOSS</b>	N/A

**Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • [www.majicpaints.com](http://www.majicpaints.com)**

**Caution:**

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.