

**MAJIC® POLYURETHANE WOOD COATING CLEAR SPRAY****FEATURES**

- Wear & weather resistant
- Protects finish from abrasion, water, alcohol, cleaners and stains
- Hard protective finish
- Enriches the natural beauty of the wood

**DESCRIPTION & USES**

A hard protective finish which offers long lasting beauty. This product provides a finish that is resistant to water, chemicals, detergents, alcohol, impact and abrasion. Formulated and recommended for application on bare wood to seal the wood and to provide a coating that can be sanded to create a smooth surface.

**PRODUCTS & SIZES**

8-20300 Clear Gloss, 8-20386 Clear Satin. Available in 11 oz sprays.

**SURFACE PREPARATION**

New wood should be sanded thoroughly. Remove all traces of dust with a tack cloth. On previously finished wood, remove any shellac, lacquer or varnish with paint remover. All wax, grease or dust must be removed. Any finish in poor condition must be sanded smooth. Sand surface thoroughly and remove sanding dust with a tack cloth.

**APPLICATION**

Always apply paint at room temperature (70° to 80° F). To ensure color uniformity and prevent clogging. SHAKE CAN vigorously for at least one minute after mixing ball rattles. Hold can in an upright position 10" to 16" from the object being sprayed. Press spray button with a twisting motion with top of can and spray button opening pointed away from you. Always clean spray button immediately after use by turning can upside down and pressing spray button until no more paint comes out.

**PHYSICAL PROPERTIES**

<b>RESIN TYPE</b>	Alkyd
<b>SOLVENT</b>	Refer to MSDS
<b>VOC / MIR (sprays)</b>	<1.50
<b>FILM THICKNESS</b>	<b>Mils Wet-</b> N/A
	<b>Mils Dry-</b> N/A
<b>COVERAGE</b>	Up to 24 sq ft/can @ 1mil
<b>DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY</b>	10 Hours <b>To Touch</b>
	12 Hours <b>To Recoat</b>
<b>VISCOSITY</b>	N/A
<b>FLASH POINT</b>	< 50° F
<b>FINISH</b>	Gloss / Satin
<b>GLOSS</b>	Gloss: 80+@ 60°
	Satin: 18-25@ 60°

**Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • [www.majicpaints.com](http://www.majicpaints.com)**

**Caution:**

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.