

TECHNICAL DATA

8-20850 Series

MAJIC[®] CAMOUFLAGE SPRAY PAINT

FEATURES

٠

- Flat, non-reflective finish
- Water resistant
- Provides camouflage with any nature background
- Perfect for use on vehicles, boats, trailers, duck blinds, free stands, ladders, ladder stands, guns, bows, etc.

DESCRIPTION & USES

Majic Camouflage Spray Paint offers a flat, non-reflective finish that is rust inhibiting and water resistant to protect wood and metal from the elements. The color selection is perfect for breaking up outlines and shapes with camouflage allowing you to blend with almost any nature background.

PRODUCTS & SIZES

8-20850 Olive Drab, 8-20851 Black, 8-20852 Khaki, 8-20853 Bark Gray, 8-20854 Earth Brown, 8-20855 Desert Tan. Available in 12 oz sprays.

SURFACE PREPARATION

Bare Metal: Remove all rust scale with wire brush or sander. Remove oil or grease with paint thinner. Prime with rust inhibiting primer. Painted Metal: Remove loose or peeling paint and rust scale with wire brush or sander. Remove oil or grease with paint thinner. Prime any bare metal with rust inhibiting primer. Painted Surfaces: (General) Make sure surface is clean, dry and free of loose paint, dirt, wax, grease, etc. Sand glossy areas. Spot prime absorbent areas. Surface must be dry and free of dirt, dust, grease or wax. Protect surrounding areas with drop cloths. Always apply paint at room temperature (70°-80° F). To ensure color uniformity and prevent clogging, SHAKE CAN vigorously for at least one minute after mixing ball rattles. Hold can in an upright position 10" to 16" from the object being sprayed. Press spray button firmly. Use steady, even strokes while spraying. Several thin coats will result in a better finish than one heavy coat. If clogging develops remove spray button with a twisting motion and clean in mineral spirits. DO NOT STICK PIN OR OTHER OBJECT INTO CAN. Gently replace spray button with a twisting motion with top of can and spray button opening pointed away from you. Always clean spray button immediately after use by turning can upside down and pressing spray button until no more paint comes out.

PHYSICAL PROPERTIES

	Allored
RESIN TYPE	Alkyd
SOLVENT	Refer to MSDS
VOC / MIR (sprays)	< 1.20 grams/liter
FILM THICKNESS	Mils Wet- N/A
	Mils Dry- N/A
COVERAGE	8.5 sq ft/can
DRY TIMES AT 77°F AND	1-2 Hours To Touch
50% RELATIVE HUMIDITY	2-4 Hours To Recoat
VISCOSITY	N/A
FLASH POINT	< 50° F
FINISH	Flat

Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.

APPLICATION