

## MAJIC® EASY SPREAD

### Exterior Latex Flat Primer

#### FEATURES

- Provides an excellent base coat for latex, acrylic, and alkyd finish
- Tools rinse clean in soapy water
- Applies easily

#### DESCRIPTION & USES

A specially formulated undercoat for use on wood, masonry, brick and metal. Easy Spread Exterior Latex Flat Primer provides an excellent base for latex, acrylic and alkyd house paints. This product provides the important first step for a long lasting paint system that is blister and peel resistant.

#### PRODUCTS & SIZES

8-2090 White, 8-2029. Available in gallon and 2 gallon containers.

#### SURFACE PREPARATION

The surface must be dry and free of peeling paint, loose rust, excessive chalk, wax or mildew. Fill cracks and nail holes with patching compound and sand smooth. Spot prime knots and rusty nail heads with a shellac type primer to prevent bleed through. Sand scraped areas to promote a more even finish. Sand glossy areas. Thoroughly wash the surface with detergent and water, remove dirt, sanding dust, chalk and pollutants. Remove any mildew using one quart of household bleach in three quarts of water. Rinse and let dry thoroughly. Wear goggles and gloves to prevent contact with the bleach. Allow washed areas to dry at least 48 hours before applying this primer. NOTE: Caulking, puttying and glazing are best done after Easy Spread Exterior Latex Primer has been applied and allowed to dry completely.

#### APPLICATION

Stir paint thoroughly until uniform. Apply with a good quality brush or roller making sure to get this primer on all exposed surfaces. Do not paint if the surface temperature is below 50° F or if rain is expected within 24 hours. DO NOT THIN.

#### PHYSICAL PROPERTIES

RESIN TYPE	Vinyl/Acrylic Latex/Alkyd
SOLVENT	Water
GLOSS	2-8 @ 60°
VOC	<100 grams/liter
FILM THICKNESS	4.0 Mils <b>Wet</b> 1.3 Mils <b>Dry</b>
COVERAGE	Up to 400 sq ft/gal
DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY	1-2 Hours <b>To Touch</b> 8 Hours <b>To Recoat</b> 7-10 Days <b>Full Cure</b>
VISCOSITY	80-85 KU
FLASH POINT	> 200°F
FINISH	Flat

**Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • [www.majicpaints.com](http://www.majicpaints.com)**

#### Caution:

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.