

## **MAJIC® TOWN & COUNTRY®** Clear Coat High Gloss Lacquer Spray

### FEATURES

- Provides protection and fade resistance when applied over Majic Tractor, Truck & Implement Enamel that has fully cured for at least 7 days.

### DESCRIPTION & USES

Town & Country Clear Coat High Gloss Lacquer Spray is a non-yellowing gloss finish that provides additional protection and fade resistance. Apply over Majic Tractor, Truck & Implement Enamel that has cured for at least 7 days. Not waiting for the full cure time of the enamel will cause lifting and wrinkling of the finish coat.

### PRODUCTS & SIZES

8-20999 Clear. Available in 11 oz sprays.

### SURFACE PREPARATION

Surface must be dry and free of dirt, dust, grease or wax. Protect surrounding areas with drop cloths. Always apply paint at room temperature (70°-80° F).

### APPLICATION

To ensure color uniformity and prevent clogging, SHAKE CAN vigorously for at least one minute after mixing ball rattles. Hold can in an upright position 10" to 16" from the object being sprayed. Press spray button firmly. Use steady, even strokes while spraying. Several thin coats will result in a better finish than one heavy coat. If clogging develops, remove spray button with a twisting motion and clean in mineral spirits. DO NOT STICK PIN OR OTHER OBJECT INTO CAN. Gently replace spray button with a twisting motion with top of can and spray button opening pointed away from you. Always clean spray button immediately after use by turning can upside down and pressing spray button until no more paint comes out.

### PHYSICAL PROPERTIES

<b>RESIN TYPE</b>	Refer to MSDS
<b>SOLVENT</b>	Refer to MSDS
<b>VOC / MIR (sprays)</b>	<1.50
<b>FILM THICKNESS</b>	<b>Mils Wet-</b> N/A <b>Mils Dry-</b> N/A
<b>COVERAGE</b>	20-30 sq ft/can
<b>DRY TIMES AT 77°F AND 50% RELATIVE HUMIDITY</b>	3-4 Hours <b>To Touch</b> 8 Hours <b>To Recoat</b>
<b>VISCOSITY</b>	N/A
<b>FLASH POINT</b>	< 50° F
<b>FINISH</b>	High Gloss
<b>GLOSS</b>	85+@ 60°

**Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • [www.majicpaints.com](http://www.majicpaints.com)**

**Caution:**

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.