

# **TECHNICAL DATA**

8-21500 Series

# MAJIC® DIAMONDHARD® Spray Enamel

## **FEATURES**

- Levels like glass
- Sticks to: plastic, glass, vinyl, tile, aluminum, brick, concrete, steel, copper, wood, masonry, many hard to paint surfaces

## **DESCRIPTION & USES**

Majic Diamondhard Spray Enamel is truly one of the finest quality general purpose coatings available today. Featuring superior adhesion to almost any interior or exterior surface, it has a resilient durable finish that lasts for years.

#### **PRODUCTS & SIZES**

8-21500 Gloss White, 8-21501 Gloss Black, 8-21502 Gloss Brown, 8-21503 Gloss Beige, 8-21505 Blue, 8-21506 Gloss Red, 8-21508 Yellow, 8-21509 Gloss Dark Gray, 8-21517 Green, 8-21520 Satin White, 8-21521 Satin Black. Available in 11 oz sprays.

#### **SURFACE PREPARATION**

Surface must be dry and free of rust, oxide, dirt, dust, grease or wax. For New or Unweathered Plastic Surfaces: Quickly wipe surface with enamel deglosser. For Aged or Weathered Plastic Surfaces: Wipe surface with ammonia based product such as window cleaner.

#### **APPLICATION**

Protect surrounding areas with drop cloths. Always apply paint at room temperature (70-80° F). To ensure color uniformity and prevent clogging, SHAKE CAN vigorously for at least two minutes after the mixing ball rattles Hold can in an upright position 8" to 10" from the object being sprayed. Press spray button firmly. Use steady, even strokes while spraying. Apply multiple thin coats and let dry between each coat to avoid runs and sags.

#### **PHYSICAL PROPERTIES**

RESIN TYPE	Refer to MSDS
SOLVENT	Refer to MSDS
VOC / MIR (sprays)	< 1.40 grams/liter
FILM THICKNESS	Mils Wet- N/A
	Mils Dry- N/A
COVERAGE	Up to 20 sq ft/can @ 1 mil
DRY TIMES AT 77°F AND	3 Hours <b>To Touch</b>
50% RELATIVE HUMIDITY	Before 24 Hours <b>To Recoat</b>
VISCOSITY	N/A
FLASH POINT	< 50° F
FINISH	Gloss / Satin
GLOSS	75+@ 60°
	20-30 @ 60°

#### Majic Paints • 201 Janus Road • Cary, IL 60013 • 847-639-5383 • www.majicpaints.com

#### Caution:

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The information and specifications stated here are for the material currently offered, are subject to change without prior notice, and, due to variations in user handling and application methods, should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, expressed or implied, concerning this product or its use either individually or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user ensures that workplace and disposal practices are in compliance with laws, regulations, and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENT OR CONSEQUENTIAL DAMAGES.